Skip to content TEXTURE_UL_texpaintslots(UIList)

```
base classes — bpy_struct, UIList
class bpy.types.TEXTURE UL texpaintslots(UIList)
     draw item( context, layout, data, item, icon, active data, active propname, index)
    classmethod bl rna get subclass(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The RNA type or default when not found.
        RETURN TYPE:
             bpy.types.Struct subclass
    classmethod bl_rna_get_subclass_py(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The class or default when not found.
        RETURN TYPE:
             type
```

Inherited Properties

bpy_struct.id_data
UIList.bl_idname
UIList.list_id
UIList.layout_type
UIList.use_filter_sort_alpha
UIList.use_filter_sort_reverse
UIList.use_filter_sort_lock
UIList.bitflag_filter_item

Inherited Functions

• bpy_struct.as_pointer • bpy struct.path resolve • bpy struct.driver add • bpy struct.pop • bpy struct.driver remove • bpy struct.property overridable library set • bpy_struct.get • bpy_struct.property_unset • bpy struct.id properties clear • bpy struct.type recast • bpy_struct.id_properties_ensure • bpy struct.values • bpy struct.id properties ui • UIList.draw item • bpy struct.is property hidden • UIList.draw filter • bpy_struct.is_property_overridable_library • UIList.filter_items • bpy struct.is property readonly • UIList.append • bpy_struct.is_property_set • UIList.is extended • bpy_struct.items

• UIList.prepend

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- UIList.remove
- UIList.bl_rna_get_subclass
- UIList.bl_rna_get_subclass_py

Previous SurfaceModifier(Modifier) Report issue on this page Copyright © Blender Authors Made with Furo TEXTURE_UL_texslots(UILi