LaplacianDeformModifier(Modifier)

base classes — `bpy_struct`, `Modifier`

class bpy.types.**LaplacianDeformModifier(Modifier)**

Mesh deform modifier

invert_vertex_group

Invert vertex group influence

TYPE:

boolean, default False

is_bind

Whether geometry has been bound to anchors

TYPE:

boolean, default False, (readonly)

iterations

TYPE:

int in [0, inf], default 1

vertex_group

Name of Vertex Group which determines Anchors

TYPE:

string, default "", (never None)

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod bl_rna_get_subclass_py(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.type`
- `Modifier.show_viewport`
- `Modifier.show_expanded`
- `Modifier.is_active`
- `Modifier.use_pin_to_last`
- `Modifier.is_override_data`

- Modifier.show_render
- Modifier.show_in_editmode
- Modifier.show_on_cage
- Modifier.use_apply_on_spline
- Modifier.execution_time
- Modifier.persistent_uid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.id_properties_clear
- bpy_struct.id_properties_ensure
- bpy_struct.id_properties_ui
- bpy_struct.is_property_hidden
- bpy_struct.is_property_overridable_library
- bpy_struct.is_property_readonly
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.pop
- bpy_struct.property_overridable_library_set
- bpy_struct.property_unset
- bpy_struct.type_recast
- bpy_struct.values
- Modifier.bl_rna_get_subclass
- Modifier.bl_rna_get_subclass_py