

[Skip to content](#)

# GeometryNodeFilletCurve(GeometryNode)

base classes — [bpy\\_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

**class** bpy.types.GeometryNodeFilletCurve(GeometryNode)

Round corners by generating circular arcs on each control point

**mode**

How to choose number of vertices on fillet

- `BEZIER` Bézier – Align Bézier handles to create circular arcs at each control point.
- `POLY` Poly – Add control points along a circular arc (handle type is vector if Bézier Spline).

**TYPE:**

enum in ['BEZIER', 'POLY'], default 'BEZIER'

**classmethod** `is_registered_node_type()`

True if a registered node type

**RETURNS:**

Result

**RETURN TYPE:**

boolean

**classmethod** `input_template(index)`

Input socket template

**PARAMETERS:**

**index** (*int* in  $[0, \infty]$ ) – Index

**RETURNS:**

result

**RETURN TYPE:**

[NodeInternalSocketTemplate](#)

**classmethod** `output_template(index)`

Output socket template

**PARAMETERS:**

**index** (*int* in  $[0, \infty]$ ) – Index

**RETURNS:**

result

**RETURN TYPE:**

[NodeInternalSocketTemplate](#)

**classmethod** `bl_rna_get_subclass(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The RNA type or default when not found.

**RETURN TYPE:**

[bpy.types.Struct](#) subclass

**classmethod** `bl_rna_get_subclass_py(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The class or default when not found.

**RETURN TYPE:**

type

## Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

## Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_to_id`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`

- `bpy_struct.patn_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)  
[GeometryNodeFillCurve\(GeometryNode\)](#)  
[Report issue on this page](#)

Copyright © Blender Authors  
 Made with [Furo](#)

[Next](#)  
[GeometryNodeFlipFaces\(GeometryNode\)](#)