Skip to content WeldModifier(Modifier)

```
base classes — bpy_struct, Modifier
class bpy.types.WeldModifier(Modifier)
    Weld modifier
     invert vertex group
         Invert vertex group influence
         TYPE:
              boolean, default False
     loose_edges
         Collapse edges without faces, cloth sewing edges
         TYPE:
              boolean, default False
     merge_threshold
         Limit below which to merge vertices
         TYPE:
              float in [0, inf], default 0.001
     mode
         Mode defines the merge rule
         • ALL All – Full merge by distance.
         \bullet \ \ \mbox{CONNECTED} \ \mbox{Connected} - \mbox{Only merge along the edges}.
         TYPE:
              enum in ['ALL', 'CONNECTED'], default 'ALL'
     vertex_group
         Vertex group name for selecting the affected areas
         TYPE:
              string, default ", (never None)
     classmethod bl_rna_get_subclass(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
         RETURNS:
              The RNA type or default when not found.
         RETURN TYPE:
              bpy.types.Struct subclass
     classmethod bl rna get subclass py(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
```

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

•	bpy	struct.	.id	data
---	-----	---------	-----	------

• Modifier.name

• Modifier.type

Modifier.show_viewport

• Modifier.show render

• Modifier.show in editmode • Modifier.execution time

• Modifier.show on cage

• Modifier.show expanded

• Modifier.is active

• Modifier.use pin to last

• Modifier.is override data

Modifier.use apply_on_spline

• Modifier.persistent uid

Inherited Functions

• bpy struct.as pointer

• bpy struct.driver add

• bpy struct.driver remove

• bpy struct.get

• bpy struct.id properties clear

• bpy struct.id properties ensure

• bpy struct.id properties ui

• bpy_struct.is_property_hidden

• bpy struct.is property overridable library • bpy struct.type recast

• bpy struct.is property readonly

• bpy struct.is property set

• bpy struct.items

• bpy struct.keyframe delete

• bpy struct.keyframe insert

• bpy struct.keys

• bpy struct.path from id

• bpy struct.path resolve

• bpy struct.pop

• bpy struct.property overridable library set

• bpy_struct.property_unset

• bpy struct.values

• Modifier.bl rna get subclass

• Modifier.bl rna get subclass py

Previous WeightedNormalModifier(Modifier) Report issue on this page

Copyright © Blender Authors Made with Furo

WhiteBalanceModifier(StripModifier)