

[Skip to content](#)

BlendDataScenes(bpy_struct)

base class — `bpy_struct`

class `bpy.types.BlendDataScenes(bpy_struct)`

Collection of scenes

new(name)

Add a new scene to the main database

PARAMETERS:

name (*string, (never None)*) – New name for the data-block

RETURNS:

New scene data-block

RETURN TYPE:

`Scene`

remove(scene, *, do_unlink=True)

Remove a scene from the current blendfile

PARAMETERS:

- **scene** (`Scene`, (never None)) – Scene to remove
- **do_unlink** (*boolean, (optional)*) – Unlink all usages of this scene before deleting it

tag(value)

tag

PARAMETERS:

value (*boolean*) – Value

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.id_properties_ui](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_overridable_library](#)
- [bpy_struct.is_property_readonly](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [BlendData.scenes](#)