

[Skip to content](#)

GreasePencilLayerGroup(bpy_struct)

base class — [bpy_struct](#)

class bpy.types.GreasePencilLayerGroup(bpy_struct)

Group of Grease Pencil layers

channel_color

TYPE:

[mathutils.Color](#) of 3 items in [0, inf], default (0.0, 0.0, 0.0)

color_tag

TYPE:

enum in ['NONE', 'COLOR1', 'COLOR2', 'COLOR3', 'COLOR4', 'COLOR5', 'COLOR6', 'COLOR7', 'COLOR8'], default 'COLOR1'

hide

Set layer group visibility

TYPE:

boolean, default False

is_expanded

The layer groups is expanded in the UI

TYPE:

boolean, default False

lock

Protect group from further editing and/or frame changes

TYPE:

boolean, default False

name

Group name

TYPE:

string, default "", (never None)

parent_group

The parent group this group is part of

TYPE:

[GreasePencilLayerGroup](#), (readonly)

use_masks

The visibility of drawings in the layers in this group is affected by the layers in the masks lists

TYPE:

boolean, default False

use_onion_skinning

Display onion skins before and after the current frame

TYPE:

.....

boolean, default False

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `GreasePencilLayer.parent_group`
- `GreasePencilLayerGroup.parent_group`
- `GreasePencilv3.layer_groups`
- `GreasePencilv3LayerGroup.active`
- `GreasePencilv3LayerGroup.move`
- `GreasePencilv3LayerGroup.move_bottom`
- `GreasePencilv3LayerGroup.move_to_layer_group`
- `GreasePencilv3LayerGroup.move_to_layer_gro`
- `GreasePencilv3LayerGroup.move_top`
- `GreasePencilv3LayerGroup.new`
- `GreasePencilv3LayerGroup.new`
- `GreasePencilv3LayerGroup.remove`
- `GreasePencilv3Layers.move_to_layer_group`
- `GreasePencilv3Layers.new`

[Previous](#)
[GreasePencilLayer\(bpy_struct\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[GreasePencilLayerMask\(bpy_struct\)](#)