

LineStyleThicknessModifier_Material(LineStyleThicknessModifier)

base classes — [bpy_struct](#), [LineStyleModifier](#), [LineStyleThicknessModifier](#)

class bpy.types.LineStyleThicknessModifier_Material(LineStyleThicknessModifier)

Change line thickness based on a material attribute

blend

Specify how the modifier value is blended into the base value

TYPE:

enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'DIFFERENCE', 'MINIMUM', 'MAXIMUM'], default 'MIX'

curve

Curve used for the curve mapping

TYPE:

[CurveMapping](#), (readonly)

expanded

True if the modifier tab is expanded

TYPE:

boolean, default False

influence

Influence factor by which the modifier changes the property

TYPE:

float in [0, 1], default 0.0

invert

Invert the fade-out direction of the linear mapping

TYPE:

boolean, default False

mapping

Select the mapping type

- `LINEAR` Linear – Use linear mapping.
- `CURVE` Curve – Use curve mapping.

TYPE:

enum in ['LINEAR', 'CURVE'], default 'LINEAR'

material_attribute

Specify which material attribute is used

TYPE:

enum in ['LINE', 'LINE_R', 'LINE_G', 'LINE_B', 'LINE_A', 'DIFF', 'DIFF_R', 'DIFF_G', 'DIFF_B', 'SPEC', 'SPEC_R', 'SPEC_G', 'SPEC_B', 'SPEC_HARD', 'ALPHA'], default 'LINE'

type

Type of the modifier

type of the modifier

TYPE:

enum in [LineStyle Thickness Modifier Type Items](#), default 'ALONG_STROKE', (readonly)

use

Enable or disable this modifier during stroke rendering

TYPE:

boolean, default False

value_max

Maximum output value of the mapping

TYPE:

float in [-inf, inf], default 0.0

value_min

Minimum output value of the mapping

TYPE:

float in [-inf, inf], default 0.0

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

[type](#)

Inherited Properties

- [bpy_struct.id_data](#) • [LineStyleThicknessModifier.name](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)

- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `LineStyleModifier.bl_rna_get_subclass`
- `LineStyleModifier.bl_rna_get_subclass_py`
- `LineStyleThicknessModifier.bl_rna_get_subcla`
- `LineStyleThicknessModifier.bl_rna_get_subcla`

[Previous](#)

[LineStyleThicknessModifier_DistanceFromObject\(LineStyleThicknessModifier\)](#)

Copyright [LineStyleThicknessModifier_Noise\(LineStyleThicknessModifi](#)

© Blender

Authors

Made with [Furo](#)

[Report issue on this page](#)

