ObjectLightLinking(bpy_struct)

base class — `bpy_struct`

class bpy.types.**ObjectLightLinking(bpy_struct)**

> **blocker_collection**
>
> > Collection which defines objects which block light from this emitter
> >
> > **TYPE:**
> >
> > > `Collection`
>
> **receiver_collection**
>
> > Collection which defines light linking relation of this emitter
> >
> > **TYPE:**
> >
> > > `Collection`
>
> **classmethod bl_rna_get_subclass(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The RNA type or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > `bpy.types.Struct` subclass
>
> **classmethod bl_rna_get_subclass_py(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The class or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`

- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.light_linking`

Copyright © Blender Authors
Made with Furo

Report issue on this page