

[Skip to content](#)

NodeOutputFileSlotFile(bpy_struct)

base class — `bpy_struct`

class `bpy.types.NodeOutputFileSlotFile(bpy_struct)`

Single layer file slot of the file output node

format

TYPE:

`ImageFormatSettings`, (readonly)

path

Subpath used for this slot

TYPE:

string, default “”, (never None)

save_as_render

Apply render part of display transform when saving byte image

TYPE:

boolean, default False

use_node_format

TYPE:

boolean, default False

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.id_properties_ui](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_overridable_library](#)
- [bpy_struct.is_property_readonly](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [CompositorNodeOutputFile.file_slots](#)