

[Skip to content](#)

MovieTrackingObjects(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MovieTrackingObjects(bpy_struct)`

Collection of movie tracking objects

active

Active object in this tracking data object

TYPE:

`MovieTrackingObject`

new(name)

Add tracking object to this movie clip

PARAMETERS:

name (*string, (never None)*) – Name of new object

RETURNS:

New motion tracking object

RETURN TYPE:

`MovieTrackingObject`

remove(object)

Remove tracking object from this movie clip

PARAMETERS:

object (`MovieTrackingObject` , (never None)) – Motion tracking object to be removed

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `MovieTracking.objects`