## PrimitiveFloat(bpy\_struct)

```
base class — bpy_struct
class bpy.types.PrimitiveFloat(bpy struct)
    RNA wrapped float
     value
         TYPE:
             float in [-inf, inf], default 0.0, (readonly)
     classmethod bl rna get subclass(id, default=None)
         PARAMETERS:
             id (str) – The RNA type identifier.
         RETURNS:
             The RNA type or default when not found.
         RETURN TYPE:
              bpy.types.Struct subclass
     classmethod bl_rna_get_subclass_py(id, default=None)
         PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The class or default when not found.
         RETURN TYPE:
             type
```

## **Inherited Properties**

• bpy struct.id data

## **Inherited Functions**

• bpy struct.as pointer • bpy struct.items • bpy struct.driver add • bpy struct.keyframe delete • bpy struct.driver remove • bpy struct.keyframe insert • bpy struct.get • bpy struct.keys • bpy\_struct.id\_properties\_clear • bpy\_struct.path\_from\_id • bpy struct.id properties ensure • bpy struct.path resolve • bpy\_struct.id\_properties\_ui • bpy\_struct.pop • bpy struct.is property hidden • bpy struct.property overridable library set • bpy struct.is property overridable library • bpy struct.property unset • bpy\_struct.type\_recast bpy struct.is property readonly • bpy struct.is property set • bpy struct.values

PrimitiveBoolean(bpy\_struct)
Report issue on this page

Made with Furo