

[Skip to content](#)

LibraryWeakReference(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.LibraryWeakReference(bpy_struct)`

Read-only external reference to a linked data-block and its library file

filepath

Path to the library .blend file

TYPE:

string, default ‘’, (readonly, never None)

id_name

Full ID name in the library .blend file (including the two leading ‘id type’ chars)

TYPE:

string, default ‘’, (readonly, never None)

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.id_properties_ui](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_get](#)

- bpy_struct.is_property_hidden
- bpy_struct.is_property_override_library
- bpy_struct.is_property_readonly
- bpy_struct.is_property_set
- bpy_struct.property_override_library_set
- bpy_struct.property_unset
- bpy_struct.type_recast
- bpy_struct.values

References

- [ID.library_weak_reference](#)