

[Skip to content](#)

# GeometryNodeInputNormal(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

**class** bpy.types.GeometryNodeInputNormal(GeometryNode)

Retrieve a unit length vector indicating the direction pointing away from the geometry at each element

**legacy\_corner\_normals**

Always use face normals for the face corner domain, matching old behavior of the node

**TYPE:**

boolean, default False

**classmethod** is\_registered\_node\_type()

True if a registered node type

**RETURNS:**

Result

**RETURN TYPE:**

boolean

**classmethod** input\_template(index)

Input socket template

**PARAMETERS:**

**index** (*int in [0, inf]*) – Index

**RETURNS:**

result

**RETURN TYPE:**

`NodeInternalSocketTemplate`

**classmethod** output\_template(index)

Output socket template

**PARAMETERS:**

**index** (*int in [0, inf]*) – Index

**RETURNS:**

result

**RETURN TYPE:**

`NodeInternalSocketTemplate`

**classmethod** bl\_ma\_get\_subclass(id, default=None)

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The RNA type or default when not found.

**RETURN TYPE:**

`bpy.types.Struct` subclass

**classmethod** bl\_ma\_get\_subclass\_py(id, default=None)

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The class or default when not found.

**RETURN TYPE:**

type

## Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

## Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`

- [bpy\\_struct.property\\_unset](#)
- [bpy\\_struct.type\\_recast](#)
- [bpy\\_struct.values](#)
- [Node.socket\\_value\\_update](#)
- [Node.is\\_registered\\_node\\_type](#)
- [Node.poll](#)

- [NodeInternal.draw\\_buttons\\_ext](#)
- [NodeInternal.bl\\_rna\\_get\\_subclass](#)
- [NodeInternal.bl\\_rna\\_get\\_subclass\\_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl\\_rna\\_get\\_subclass](#)
- [GeometryNode.bl\\_rna\\_get\\_subclass\\_py](#)

[Previous](#)

[GeometryNodeInputNamedLayerSelection\(GeometryNode\)](#)

[Report issue on this page](#)

Copyright © Blender Authors

Made with [Furo](#)

[GeometryNodeInputObject\(GeometryNode\)](#)

[Next](#)