Skip to content Lattice Modifier (Modifier)

```
base classes — bpy_struct, Modifier
class bpy.types.LatticeModifier(Modifier)
    Lattice deformation modifier
     invert vertex group
         Invert vertex group influence
         TYPE:
              boolean, default False
     object
         Lattice object to deform with
         TYPE:
              Object
     strength
         Strength of modifier effect
         TYPE:
              float in [-inf, inf], default 1.0
     vertex_group
         Name of Vertex Group which determines influence of modifier per point
         TYPE:
              string, default ", (never None)
     classmethod bl rna get subclass(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
         RETURNS:
              The RNA type or default when not found.
         RETURN TYPE:
              bpy.types.Struct subclass
     classmethod bl rna get subclass py(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
         RETURNS:
              The class or default when not found.
         RETURN TYPE:
              type
```

Inherited Properties

bpy_struct.id_data
 Modifier.show_expanded
 Modifier.is_active
 Modifier.is_active

Modifier.use_pin_to_tast Moailier.type • Modifier.show_viewport • Modifier.is_override_data • Modifier.show render • Modifier.use_apply_on_spline • Modifier.show in editmode • Modifier.execution time

Modifier.persistent uid

Inherited Functions

• bpy struct.as pointer • bpy struct.driver add

• Modifier.show on cage

- bpy struct.driver remove
- bpy_struct.get
- bpy struct.id properties clear
- bpy_struct.id_properties_ensure
- bpy struct.id properties ui
- bpy struct.is property hidden
- bpy_struct.is_property_overridable_library bpy_struct.type_recast
- bpy struct.is property readonly
- bpy struct.is property set
- bpy_struct.items

- bpy struct.keyframe delete
- bpy struct.keyframe insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy struct.path resolve
- bpy struct.pop
- bpy struct.property overridable library set
- bpy struct.property unset
- bpy struct.values
- Modifier.bl rna get subclass
- Modifier.bl_rna_get_subclass_py

Previous Lattice(ID)

Report issue on this page

Copyright © Blender Authors Made with Furo

No LatticePoint(bpy stru