

[Skip to content](#)

ActionLayers(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.ActionLayers(bpy_struct)`

Collection of animation layers

new(name)

Add a layer to the Animation. Currently an Animation can only have at most one layer.

PARAMETERS:

name (*string, (never None)*) – Name, Name of the layer, will be made unique within the Action

RETURNS:

Newly created animation layer

RETURN TYPE:

[ActionLayer](#)

remove(anim_layer)

Remove the layer from the animation

PARAMETERS:

anim_layer ([ActionLayer](#)) – Animation Layer, The layer to remove

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)

- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Action.layers`

[Previous](#)
[ActionLayer\(bpy_struct\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[ActionPoseMarkers\(bpy_struct\)](#)