Skip to content

LineStyleGeometryModifiers(bpy_struct)

```
base class — bpy_struct
```

class bpy.types.LineStyleGeometryModifiers(bpy_struct)

Geometry modifiers for changing line geometries

new(name, type)

Add a geometry modifier to line style

PARAMETERS:

- name (string, (never None)) New name for the geometry modifier (not unique)
- type (enum in Linestyle Geometry Modifier Type Items) Geometry modifier type to add

RETURNS:

Newly added geometry modifier

RETURN TYPE:

LineStyleGeometryModifier

remove(modifier)

Remove a geometry modifier from line style

PARAMETERS:

modifier (LineStyleGeometryModifier, (never None)) - Geometry modifier to remove

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id(str) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

bpy.types.Struct subclass

classmethod bl_rna_get_subclass_py(id, default=None)

PARAMETERS:

id(str) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

• bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.driver_add

- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.driver_remove
- bpy struct.get
- bpy_struct.id_properties_clear
- bpy struct.id properties ensure
- bpy struct.id properties ui
- bpy struct.is property hidden
- bpy_struct.is_property_overridable_library bpy_struct.property_unset
- bpy struct.is property readonly
- bpy_struct.is_property_set

- bpy_struct.keyframe_insert
- bpy struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy struct.pop
- bpy struct.property overridable library set
- bpy struct.type recast
- bpy struct.values

References

• FreestyleLineStyle.geometry_modifiers

Previous LineStyleGeometryModifier TipRemover(LineStyleGeometryModifier) Report issue on this page

Copyright © Blender Authors Made with Furo

LineStyleModifier(bpy stru