NodeGroupOutput(NodeInternal)

```
base classes — bpy_struct, Node, NodeInternal
class bpy.types.NodeGroupOutput(NodeInternal)
    Output data from inside of a node group
    is active output
        True if this node is used as the active group output
        TYPE:
             boolean, default False
    classmethod is_registered_node_type()
        True if a registered node type
        RETURNS:
             Result
        RETURN TYPE:
             boolean
    classmethod input_template(index)
        Input socket template
        PARAMETERS:
             index (int in [0, inf]) – Index
        RETURNS:
             result
        RETURN TYPE:
             NodeInternalSocketTemplate
    classmethod output_template(index)
        Output socket template
        PARAMETERS:
             index (int in [0, inf]) – Index
        RETURNS:
             result
        RETURN TYPE:
             NodeInternalSocketTemplate
    classmethod bl_rna_get_subclass(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The RNA type or default when not found.
        RETURN TYPE:
             bpy.types.Struct subclass
```

classmethod bl rna get subclass py(id, default=None)

PARAMETERS:

```
id (str) – The RNA type identifier.
```

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- bpy struct.id data
- Node.type
- Node.location
- Node.location absolute Node.hide
- Node.width
- Node.height
- Node.dimensions
- Node.name
- Node.label
- Node.inputs
- Node.outputs
- Node.parent
- Node.warning_propagation Node.bl_width_max

Inherited Functions

- Node.color
- Node.color tag

- Node.select
 - Node.show options
- Node.show_preview

 - Node.mute
 - Node.show texture
- Node.bl idname
 - Node.bl label
- Node.bl description
- Node.bl icon
- Node.bl static type
- Node.internal_links Node.bl_width_default
 - Node.bl width min
- Node.use_custom_color Node.bl_height_default
 - Node.bl height min
 - Node.bl height max
- bpy struct.as pointer
- bpy struct.driver add
- bpy_struct.driver_remove
- bpy struct.get
- bpy struct.id properties clear
- bpy struct.id properties ensure
- bpy struct.id properties ui
- bpy struct.is property hidden
- bpy_struct.is_property_overridable_library Node.draw_buttons
- bpy struct.is property readonly
- bpy struct.is property set
- bpy_struct.items
- bpy struct.keyframe delete
- bpy_struct.keyframe_insert
- bpy struct.keys
- bpy struct.path from id
- bpy_struct.path_resolve
- bpy struct.pop
- bpy struct.property overridable library set NodeInternal.update

- Node.is registered node type
- Node.poll
- Node.poll_instance
- Node.update
- Node.insert link
- Node.init
- Node.copy
- Node.free
- Node.draw buttons ext
- Node.draw label
- Node.debug_zone_body_lazy_function_graph
- Node.debug_zone_lazy_function_graph
- Node.poll
- Node.bl rna get subclass
- Node.bl rna get subclass py
- NodeInternal.poll
- NodeInternal.poll instance

- bpy_struct.property_unset
- bpy_struct.type_recast
- bpy_struct.values
- Node.socket_value_update

- NodeInternal.draw buttons
- NodeInternal.draw_buttons_ext
- NodeInternal.bl_rna_get_subclass
- NodeInternal.bl_rna_get_subclass_py

Previous
NodeGroupInput(NodeInternal)
Report issue on this page

Copyright © Blender Authors Made with Furo NodeIndexSwitchItems(bpy_stru