## Skip to content TextStrip(EffectStrip)

```
base classes — bpy_struct, Strip, EffectStrip
class bpy.types.TextStrip(EffectStrip)
     Sequence strip creating text
     alignment x
         Horizontal text alignment
         TYPE:
               enum in ['LEFT', 'CENTER', 'RIGHT'], default 'LEFT'
     anchor_x
         Horizontal position of the text box relative to Location
         TYPE:
               enum in ['LEFT', 'CENTER', 'RIGHT'], default 'LEFT'
     anchor_y
         Vertical position of the text box relative to Location
         TYPE:
               enum in ['TOP', 'CENTER', 'BOTTOM'], default 'TOP'
     box_color
         TYPE:
               float array of 4 items in [0, inf], default (0.0, 0.0, 0.0, 0.0)
     box_margin
         Box margin as factor of image width
         TYPE:
               float in [0, 1], default 0.01
     box\_roundness
         Box corner radius as a factor of box height
          TYPE:
               float in [0, 1], default 0.0
     color
         Text color
         TYPE:
               float array of 4 items in [0, inf], default (0.0, 0.0, 0.0, 0.0)
     font
         Font of the text. Falls back to the UI font by default.
         TYPE:
               VectorFont
     font_size
```

Size of the text

```
TYPE:
         float in [0, 2000], default 0.0
input count
    TYPE:
         int in [0, inf], default 0, (readonly)
location
    Location of the text
    TYPE:
          mathutils. Vector of 2 items in [-inf, inf], default (0.0, 0.0)
outline color
    TYPE:
         float array of 4 items in [0, inf], default (0.0, 0.0, 0.0, 0.0)
outline\_width
    TYPE:
         float in [0, 1], default 0.05
shadow angle
    TYPE:
         float in [0, 6.28319], default 1.13446
shadow_blur
    TYPE:
         float in [0, 1], default 0.0
shadow\_color
    TYPE:
         float array of 4 items in [0, inf], default (0.0, 0.0, 0.0, 0.0)
shadow_offset
    TYPE:
         float in [0, 1], default 0.04
text
    Text that will be displayed
    TYPE:
         string, default ", (never None)
use\_bold
    Display text as bold
    TYPE:
         boolean, default False
use\_box
    Display colored box behind text
    TYPE:
         boolean, default False
```

usa italia

```
Display text as italic
         TYPE:
             boolean, default False
     use outline
         Display outline around text
         TYPE:
             boolean, default False
     use_shadow
         Display shadow behind text
         TYPE:
             boolean, default False
     wrap_width
         Word wrap width as factor, zero disables
         TYPE:
             float in [0, inf], default 0.0
     classmethod bl_rna_get_subclass(id, default=None)
         PARAMETERS:
             id (str) – The RNA type identifier.
         RETURNS:
             The RNA type or default when not found.
         RETURN TYPE:
              bpy.types.Struct subclass
     classmethod bl_rna_get_subclass_py(id, default=None)
         PARAMETERS:
             id (str) - The RNA type identifier.
         RETURNS:
             The class or default when not found.
         RETURN TYPE:
             type
Inherited Properties
```

use\_nanc

• bpy\_struct.id\_data Strip.color\_tag • Strip.name • Strip.modifiers • Strip.type • Strip.use cache raw • Strip.use cache preprocessed • Strip.select • Strip.select left handle • Strip.use cache composite • Strip.select\_right\_handle • Strip.override\_cache\_settings • Strip.mute • Strip.show\_retiming\_keys • Strip.lock • EffectStrip.use deinterlace • Strip.frame\_final\_duration • EffectStrip.alpha\_mode • Strip.frame duration EffectStrip.use\_flip\_x

•	Strip.frame_start •	<pre>EffectStrip.use_flip_y</pre>
•	Strip.frame_final_start •	EffectStrip.use_float
•	Strip.frame_final_end •	EffectStrip.use_reverse_frames
•	Strip.frame_offset_start •	EffectStrip.color_multiply
•	Strip.frame_offset_end •	EffectStrip.multiply_alpha
•	Strip.channel •	EffectStrip.color_saturation
•	Strip.use_linear_modifiers •	EffectStrip.strobe
•	Strip.blend_type •	EffectStrip.transform
•	Strip.blend_alpha •	EffectStrip.crop
•	Strip.effect_fader •	EffectStrip.use_proxy
•	Strip.use_default_fade •	EffectStrip.proxy

## **Inherited Functions**

•	pba <sup>-</sup>	_struct.as_poir	nter	
•	bpy	struct.driver	add	

- bpy\_struct.driver\_remove
- bpy struct.get
- bpy\_struct.id\_properties\_clear
- bpy struct.id properties ensure
- bpy struct.id properties ui
- bpy\_struct.is\_property\_hidden
- bpy\_struct.is\_property\_overridable\_library Strip.move\_to\_meta
- bpy struct.is property readonly
- bpy\_struct.is\_property\_set
- bpy struct.items
- bpy\_struct.keyframe\_delete
- bpy struct.keyframe insert
- bpy struct.keys
- bpy struct.path from id

- bpy struct.path resolve
- bpy struct.pop
- bpy\_struct.property\_overridable\_library\_set
- bpy struct.property unset
- bpy\_struct.type\_recast
- bpy struct.values
- Strip.strip\_elem\_from\_frame
- Strip.swap
- Strip.parent meta
- Strip.invalidate\_cache
- Strip.split
- Strip.bl\_rna\_get\_subclass
- Strip.bl rna get subclass py
- EffectStrip.bl rna get subclass
- EffectStrip.bl rna get subclass py

**Previous** TextLine(bpy struct)

Report issue on this page

Copyright © Blender Authors Made with Furo

Texture(I