

[Skip to content](#)

ThemeFontStyle(bpy_struct)

base class — [bpy_struct](#)

class bpy.types.ThemeFontStyle(bpy_struct)

Theme settings for Font

character_weight

Weight of the characters. 100-900, 400 is normal.

TYPE:

int in [100, 900], default 400

points

Font size in points

TYPE:

float in [6, 32], default 0.0

shadow

Shadow type (0 none, 3, 5 blur, 6 outline)

TYPE:

int in [0, 6], default 0

shadow_alpha

TYPE:

float in [0, 1], default 0.0

shadow_offset_x

Shadow offset in pixels

TYPE:

int in [-10, 10], default 0

shadow_offset_y

Shadow offset in pixels

TYPE:

int in [-10, 10], default 0

shadow_value

Shadow color in gray value

TYPE:

float in [0, 1], default 0.0

classmethod bl_ma_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ThemeStyle.panel_title`
- `ThemeStyle.tooltip`
- `ThemeStyle.widget`