SpreadsheetColumn(bpy_struct)

base class — `bpy_struct`

class bpy.types.**SpreadsheetColumn(bpy_struct)**

> Persistent data associated with a spreadsheet column

> **data_type**
>> The data type of the corresponding column visible in the spreadsheet
>>
>> **TYPE:**
>>> enum in ['INT32', 'FLOAT', 'BOOLEAN', 'INSTANCES'], default 'BOOLEAN', (readonly)

> **id**
>> Data used to identify the corresponding data from the data source
>>
>> **TYPE:**
>>> `SpreadsheetColumnID`, (readonly)

> **classmethod bl_rna_get_subclass(id, default=None)**
>> **PARAMETERS:**
>>> **id** (*str*) – The RNA type identifier.
>>
>> **RETURNS:**
>>> The RNA type or default when not found.
>>
>> **RETURN TYPE:**
>>> `bpy.types.Struct` subclass

> **classmethod bl_rna_get_subclass_py(id, default=None)**
>> **PARAMETERS:**
>>> **id** (*str*) – The RNA type identifier.
>>
>> **RETURNS:**
>>> The class or default when not found.
>>
>> **RETURN TYPE:**
>>> type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`

- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_overridable_library
- bpy_struct.is_property_readonly
- bpy_struct.is_property_set
- bpy_struct.property_overridable_library_set
- bpy_struct.property_unset
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceSpreadsheet.columns

Report issue on this page