

[Skip to content](#)

NodesModifier(Modifier)

base classes — `bpy_struct`, `Modifier`

class `bpy.types.NodesModifier(Modifier)`

bake_directory

Location on disk where the bake data is stored

TYPE:

string, default ‘’, (never None)

bake_target

Where to store the baked data

- `PACKED` Packed – Pack the baked data into the .blend file.
- `DISK` Disk – Store the baked data in a directory on disk.

TYPE:

enum in [`‘PACKED’`, `‘DISK’`], default `‘PACKED’`

bakes

TYPE:

`NodesModifierBakes` `bpy_prop_collection` of `NodesModifierBake`, (readonly)

node_group

Node group that controls what this modifier does

TYPE:

`NodeTree`

node_warnings

TYPE:

`bpy_prop_collection` of `NodesModifierWarning`, (readonly)

open_bake_data_blocks_panel

TYPE:

boolean, default `False`

open_bake_panel

TYPE:

boolean, default `False`

open_manage_panel

TYPE:

boolean, default `False`

open_named_attributes_panel

TYPE:

boolean, default `False`

open_output_attributes_panel

TYPE:

boolean, default `False`

open_warnings_panel

TYPE:

boolean, default False

panels

TYPE:

`NodesModifierPanels` `bpy_prop_collection` of `NodesModifierPanel`, (readonly)

show_group_selector

TYPE:

boolean, default False

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.type`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.show_in_editmode`
- `Modifier.show_on_cage`
- `Modifier.show_expanded`
- `Modifier.is_active`
- `Modifier.use_pin_to_last`
- `Modifier.is_override_data`
- `Modifier.use_apply_on_spline`
- `Modifier.execution_time`
- `Modifier.persistent_uid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overrideable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Modifier.bl_rna_get_subclass`
- `Modifier.bl_rna_get_subclass_py`

[Previous](#)

[Nodes\(bpy_struct\)](#)

[Report issue on this page](#)

Copyright © Blender Authors

Made with [Furo](#)

[NodesModifierBake\(bpy_struct\)](#)