Skip to content StripModifier(bpy_struct)

```
base class — bpy_struct
subclasses — BrightContrastModifier, ColorBalanceModifier, CurvesModifier, HueCorrectModifier,
SequencerTonemapModifierData, SoundEqualizerModifier, WhiteBalanceModifier
class bpy.types.StripModifier(bpy_struct)
    Modifier for sequence strip
    input_mask_id
        Mask ID used as mask input for the modifier
        TYPE:
             Mask
    input mask strip
        Strip used as mask input for the modifier
        TYPE:
             Strip
    input mask type
        Type of input data used for mask
        • STRIP Strip - Use sequencer strip as mask input.
        • ID Mask – Use mask ID as mask input.
        TYPE:
             enum in ['STRIP', 'ID'], default 'STRIP'
    mask_time
        Time to use for the Mask animation
         • RELATIVE Relative – Mask animation is offset to start of strip.
         • ABSOLUTE Absolute – Mask animation is in sync with scene frame.
        TYPE:
             enum in ['RELATIVE', 'ABSOLUTE'], default 'RELATIVE'
    mute
        Mute this modifier
        TYPE:
             boolean, default False
    name
        TYPE:
             string, default ", (never None)
    show expanded
        Mute expanded settings for the modifier
        TYPE:
```

boolean, default False

```
ijμ
    TYPE:
        enum in Strip Modifier Type Items, default 'BRIGHT CONTRAST', (readonly)
classmethod bl rna get subclass(id, default=None)
   PARAMETERS:
        id(str) – The RNA type identifier.
    RETURNS:
        The RNA type or default when not found.
    RETURN TYPE:
        bpy.types.Struct subclass
classmethod bl rna get subclass py(id, default=None)
    PARAMETERS:
        id (str) – The RNA type identifier.
    RETURNS:
        The class or default when not found.
```

Inherited Properties

RETURN TYPE: type

• bpy struct.id data

Inherited Functions

- bpy struct.as pointer • bpy_struct.driver_add • bpy struct.driver remove • bpy struct.get • bpy struct.id properties clear • bpy_struct.id_properties_ensure • bpy struct.id properties ui • bpy_struct.is_property_hidden • bpy_struct.is_property_overridable_library • bpy_struct.property_unset bpy struct.is property readonly • bpy_struct.is_property_set
 - bpy struct.items
 - bpy_struct.keyframe_delete
 - bpy struct.keyframe insert
 - bpy struct.keys
 - bpy struct.path from id
 - bpy_struct.path_resolve
 - bpy struct.pop
 - bpy_struct.property_overridable_library_set

 - bpy struct.type recast
 - bpy struct.values

References

- Strip.modifiers
 - StripModifiers.remove
- StripModifiers.new