

[Skip to content](#)

ThemeUserInterface(bpy_struct)

base class — `bpy_struct`

class bpy.types.ThemeUserInterface(bpy_struct)

Theme settings for user interface elements

axis_x

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

axis_y

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

axis_z

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

editor_border

Color of the border between editors

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

editor_outline

Color of the outline of each editor, except the active one

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

editor_outline_active

Color of the outline of the active editor

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

gizmo_a

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

gizmo_b

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

gizmo_hi

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

gizmo_primary

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

gizmo_secondary

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

gizmo_view_align

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

icon_alpha

Transparency of icons in the interface, to reduce contrast

TYPE:

float in [0, 1], default 0.0

icon_autokey

Color of Auto Keying indicator when enabled

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_border_intensity

Control the intensity of the border around themes icons

TYPE:

float in [0, 1], default 0.0

icon_collection

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_folder

Color of folders in the file browser

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_modifier

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_object

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_object_data

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_saturation

Saturation of icons in the interface

TYPE:

float in [0, 1], default 0.0

icon_scene

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

icon_shading

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

menu_shadow_fac

Blending factor for menu shadows

TYPE:

float in [0.01, 1], default 0.0

menu_shadow_width

Width of menu shadows, set to zero to disable

TYPE:

int in [0, 24], default 0

panel_roundness

Roundness of the corners of panels and sub-panels

TYPE:

float in [0, 1], default 0.4

transparent_checker_primary

Primary color of checkerboard pattern indicating transparent areas

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

transparent_checker_secondary

Secondary color of checkerboard pattern indicating transparent areas

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

transparent_checker_size

Size of checkerboard pattern indicating transparent areas

TYPE:

int in [2, 48], default 0

wcol_box

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_list_item

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_menu

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_menu_back

TYPE:

`ThemeWidgetColors`, (readonly, never None)

`ThemeWidgetColors`, (readonly, never None)

wcol_menu_item

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_num

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_numslider

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_option

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_pie_menu

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_progress

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_pulldown

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_radio

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_regular

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_scroll

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_state

TYPE:

`ThemeWidgetStateColors`, (readonly, never None)

wcol_tab

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_text

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_toggle

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_tool

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_toolbar_item

TYPE:

`ThemeWidgetColors`, (readonly, never None)

wcol_tooltip

TYPE:

`ThemeWidgetColors`, (readonly, never None)

widget_emboss

Color of the 1px shadow line underlying widgets

TYPE:

float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

widget_text_cursor

Color of the text insertion cursor (caret)

TYPE:

`mathutils.Color` of 3 items in [0, 1], default (0.0, 0.0, 0.0)

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.user_interface`