## PackedFile(bpy\_struct)

```
base class — bpy_struct
class bpy.types.PackedFile(bpy_struct)
    External file packed into the .blend file
     data
         Raw data (bytes, exact content of the embedded file)
         TYPE:
              byte string, default "o", (readonly, never None)
     size
         Size of packed file in bytes
         TYPE:
              int in [-inf, inf], default 0, (readonly)
     classmethod bl_rna_get_subclass(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
         RETURNS:
              The RNA type or default when not found.
         RETURN TYPE:
              bpy.types.Struct subclass
     classmethod bl rna get subclass py(id, default=None)
         PARAMETERS:
              id (str) – The RNA type identifier.
         RETURNS:
              The class or default when not found.
         RETURN TYPE:
              type
```

## **Inherited Properties**

• bpy struct.id data

## **Inherited Functions**

- bpy\_struct.as\_pointer
  bpy\_struct.driver\_add
  bpy\_struct.driver\_remove
  bpy\_struct.get
  bpy\_struct.id\_properties\_clear
  bpy\_struct.id\_properties\_ensure
  bpy\_struct.id\_properties\_ui
  bpy\_struct\_is\_property\_bidden
- bpy\_struct.itemsbpy\_struct.keyframe\_delete
- bpy\_struct.keyframe\_insert
- bpy\_struct.keys
- bpy\_struct.path\_from\_id
- bpy\_struct.path\_resolve
- bpy\_struct.pop
- hnu struct proportu ouorridablo libraru sot

bpy\_struct.is\_property\_mraden
 bpy\_struct.is\_property\_overridable\_library
 bpy\_struct.property\_unset
 bpy\_struct.is\_property\_readonly
 bpy\_struct.type\_recast

## References

• bpy\_struct.is\_property\_set

- Image.packed\_fileImagePackedFile.packed\_fileVectorFont.packed\_file
- Library.packed\_file Volume.packed\_file

Previous
POSE\_UL\_selection\_set(UIList)
Report issue on this page

Copyright © Blender Authors Made with Furo

• bpy\_struct.values

Paint(bpy\_stru