

base classes — `bpy_struct`, `ID`

**class** `bpy.types.Key(ID)`

Shape keys data-block containing different shapes of geometric data-blocks

**animation\_data**

Animation data for this data-block

**TYPE:**

`AnimData`, (readonly)

**eval\_time**

Evaluation time for absolute shape keys

**TYPE:**

float in [0, 1.04857e+06], default 0.0

**key\_blocks**

Shape keys

**TYPE:**

`bpy_prop_collection` of `ShapeKey`, (readonly)

**reference\_key**

**TYPE:**

`ShapeKey`, (readonly, never None)

**use\_relative**

Make shape keys relative, otherwise play through shapes as a sequence using the evaluation time

**TYPE:**

boolean, default False

**user**

Data-block using these shape keys

**TYPE:**

`ID`, (readonly, never None)

**classmethod** `bl_rna_get_subclass(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The RNA type or default when not found.

**RETURN TYPE:**

`bpy.types.Struct` subclass

**classmethod** `bl_rna_get_subclass_py(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The class or default when not found.

## RETURN TYPE:

type

## Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.name_full`
- `ID.id_type`
- `ID.session_uid`
- `ID.is_evaluated`
- `ID.original`
- `ID.users`
- `ID.use_fake_user`
- `ID.use_extra_user`
- `ID.is_embedded_data`
- `ID.is_missing`
- `ID.is_runtime_data`
- `ID.is_editable`
- `ID.tag`
- `ID.is_library_indirect`
- `ID.library`
- `ID.library_weak_reference`
- `ID.asset_data`
- `ID.override_library`
- `ID.preview`

## Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.rename`
- `ID.evaluated_get`
- `ID.copy`
- `ID.asset_mark`
- `ID.asset_clear`
- `ID.asset_generate_preview`
- `ID.override_create`
- `ID.override_hierarchy_create`
- `ID.user_clear`
- `ID.user_remap`
- `ID.make_local`
- `ID.user_of_id`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`
- `ID.preview_ensure`
- `ID.bl_rna_get_subclass`
- `ID.bl_rna_get_subclass_py`

## References

- `BlendData.shape_keys`
- `Curve.shape_keys`
- `Lattice.shape_keys`
- `Mesh.shape_keys`

