

[Skip to content](#)

ActionChannelbagGroups(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.ActionChannelbagGroups(bpy_struct)`

Collection of f-curve groups

new(name)

Create a new action group and add it to the action

PARAMETERS:

name (*string, (never None)*) – New name for the action group

RETURNS:

Newly created action group

RETURN TYPE:

[ActionGroup](#)

remove(action_group)

Remove action group

PARAMETERS:

action_group ([ActionGroup](#) , (never None)) – Action group to remove

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)

- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ActionChannelbag.groups`

[Previous](#)
[ActionChannelbagFCurves\(bpy_struct\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[ActionChannelbags\(bpy_struct\)](#)