## PropertyGroupItem(bpy\_struct)

```
base class — bpy_struct
class bpy.types.PropertyGroupItem(bpy_struct)
    Property that stores arbitrary, user defined properties
     bool
         TYPE:
              boolean, default False
     bool_array
         TYPE:
              boolean array of 1 items, default (False,)
     collection
         TYPE:
              bpy prop collection of PropertyGroup, (readonly)
     double
         TYPE:
              float in [-inf, inf], default 0.0
     double array
         TYPE:
              float array of 1 items in [-inf, inf], default (0.0)
     enum
         TYPE:
              enum in ['DEFAULT'], default 'DEFAULT'
     float
         TYPE:
              float in [-inf, inf], default 0.0
     float array
         TYPE:
              float array of 1 items in [-inf, inf], default (0.0)
     group
         TYPE:
              PropertyGroup, (readonly)
     id
         TYPE:
     idp_array
         TYPE:
              bpy_prop_collection of PropertyGroup,(readonly)
```

int

```
TYPE:
        int in [-inf, inf], default 0
int array
    TYPE:
        int array of 1 items in [-inf, inf], default (0,)
string
    TYPE:
        string, default ", (never None)
classmethod bl rna get subclass(id, default=None)
    PARAMETERS:
        id (str) – The RNA type identifier.
    RETURNS:
        The RNA type or default when not found.
    RETURN TYPE:
         bpy.types.Struct subclass
classmethod bl rna get subclass py(id, default=None)
    PARAMETERS:
        id(str) – The RNA type identifier.
    RETURNS:
        The class or default when not found.
    RETURN TYPE:
        type
```

## **Inherited Properties**

• bpy struct.id data

## **Inherited Functions**

```
• bpy struct.items
• bpy struct.as pointer
• bpy struct.driver add
                                             • bpy struct.keyframe delete
• bpy struct.driver remove
                                             • bpy struct.keyframe insert
• bpy struct.get
                                             • bpy struct.keys
• bpy struct.id properties clear
                                             • bpy struct.path from id
• bpy_struct.id_properties_ensure
                                             • bpy_struct.path_resolve
• bpy struct.id properties ui
                                             • bpy struct.pop
• bpy struct.is property hidden
                                             • bpy struct.property overridable library set
• bpy struct.is property overridable library • bpy struct.property unset
                                             • bpy_struct.type_recast
• bpy_struct.is_property_readonly
• bpy struct.is property set
                                             • bpy struct.values
```



Report issue on this page