VIEW3D_AST_brush_gpencil_weight(AssetShelf)

base classes — `bpy_struct`, `AssetShelf`

class bpy.types.**VIEW3D_AST_brush_gpencil_weight(AssetShelf)**

> **classmethod brush_type_poll(context, asset)**

> **static draw_popup_selector(layout, context, brush, show_name=True)**

> **static get_shelf_name_from_context(context)**

> **classmethod has_tool_with_brush_type(context, brush_type)**

> **classmethod bl_rna_get_subclass(id, default=None)**

>> **PARAMETERS:**
>>
>> **id** (*str*) – The RNA type identifier.
>>
>> **RETURNS:**
>>
>> The RNA type or default when not found.
>>
>> **RETURN TYPE:**
>>
>> `bpy.types.Struct` subclass

> **classmethod bl_rna_get_subclass_py(id, default=None)**

>> **PARAMETERS:**
>>
>> **id** (*str*) – The RNA type identifier.
>>
>> **RETURNS:**
>>
>> The class or default when not found.
>>
>> **RETURN TYPE:**
>>
>> type

Inherited Properties

- `bpy_struct.id_data`
- `AssetShelf.bl_idname`
- `AssetShelf.bl_space_type`
- `AssetShelf.bl_options`
- `AssetShelf.bl_activate_operator`
- `AssetShelf.bl_default_preview_size`
- `AssetShelf.asset_library_reference`
- `AssetShelf.show_names`
- `AssetShelf.preview_size`
- `AssetShelf.search_filter`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

- [bpy_struct.is_property_overridable_library](#)
- [bpy_struct.is_property_readonly](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [AssetShelf.poll](#)
- [AssetShelf.asset_poll](#)
- [AssetShelf.get_active_asset](#)
- [AssetShelf.draw_context_menu](#)
- [AssetShelf.bl_rna_get_subclass](#)
- [AssetShelf.bl_rna_get_subclass_py](#)

- [bpy_struct.is_property_overridable_library](#)
- [bpy_struct.is_property_readonly](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [AssetShelf.poll](#)
- [AssetShelf.asset_poll](#)
- [AssetShelf.get_active_asset](#)
- [AssetShelf.draw_context_menu](#)
- [AssetShelf.bl_rna_get_subclass](#)
- [AssetShelf.bl_rna_get_subclass_py](#)