

[Skip to content](#)

MeshLoopColorLayer(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.MeshLoopColorLayer(bpy_struct)`

Layer of vertex colors in a Mesh data-block

active

Sets the layer as active for display and editing

TYPE:

boolean, default False

active_render

Sets the layer as active for rendering

TYPE:

boolean, default False

data

TYPE:

[bpy_prop_collection](#) of [MeshLoopColor](#), (readonly)

name

Name of Vertex color layer

TYPE:

string, default “”, (never None)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `LoopColors.active`
- `LoopColors.remove`
- `LoopColors.new`
- `Mesh.vertex_colors`