KeyConfig(bpy_struct) base class — bpy_struct class bpy.types.KeyConfig(bpy_struct) Input configuration, including keymaps is user defined Indicates that a keyconfig was defined by the user TYPE: boolean, default False, (readonly) keymaps Key maps configured as part of this configuration TYPE: KeyMaps bpy prop collection of KeyMap, (readonly) name Name of the key configuration TYPE: string, default ", (never None) preferences TYPE: KeyConfigPreferences, (readonly) classmethod bl_rna_get_subclass(id, default=None) **PARAMETERS:** id (str) – The RNA type identifier. **RETURNS:** The RNA type or default when not found. **RETURN TYPE:** bpy.types.Struct subclass classmethod bl rna get subclass py(id, default=None) **PARAMETERS:** id(str) – The RNA type identifier. **RETURNS:** The class or default when not found. **RETURN TYPE:**

Inherited Properties

type

• bpy struct.id data

Inherited Functions

- bpy_struct.as_pointer
- bpy struct.driver_add
- bpy_struct.driver_remove
- bpy struct.get
- bpy_struct.id_properties_clear
- bpy_struct.id_properties_ensure
- bpy struct.id properties ui
- bpy_struct.is_property_hidden
- bpy struct.is_property_overridable_library bpy_struct.property_unset
- bpy_struct.is_property_readonly
- bpy_struct.is_property_set

- bpy struct.items
- bpy_struct.keyframe_delete
- bpy struct.keyframe insert
- bpy struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy struct.pop
- bpy_struct.property_overridable_library_set
- bpy_struct.type_recast
- bpy struct.values

References

- GizmoGroup.setup_keymap KeyConfigurations.new
- KeyConfigurations.active KeyConfigurations.remove
- KeyConfigurations.addon KeyConfigurations.user
- KeyConfigurations.default WindowManager.keyconfigs

Previous Key(ID)

Report issue on this page

Copyright © Blender Authors Made with Furo

KeyConfigPreferences(bpy stru