

Table of Contents

Table of Contents	1
FunctionNodeAxesToRotation(FunctionNode)	3
Inherited Properties	4
Inherited Functions	4
GeometryNodeCurveToPoints(GeometryNode)	78
Inherited Properties	79
Inherited Functions	79
GeometryNodeCustomGroup(GeometryNode)	81
Inherited Properties	81
Inherited Functions	82
GeometryNodeDeformCurvesOnSurface(GeometryNode)	83
Inherited Properties	84
Inherited Functions	84
GeometryNodeDeleteGeometry(GeometryNode)	86
Inherited Properties	87
Inherited Functions	87
GeometryNodeDistributePointsInGrid(GeometryNode)	89
Inherited Properties	90
Inherited Functions	90
GeometryNodeDistributePointsInVolume(GeometryNode)	92
Inherited Properties	93
Inherited Functions	93
GeometryNodeDistributePointsOnFaces(GeometryNode)	95
Inherited Properties	96
Inherited Functions	96
GeometryNodeDualMesh(GeometryNode)	98
Inherited Properties	99
Inherited Functions	99
GeometryNodeDuplicateElements(GeometryNode)	101
Inherited Properties	102
Inherited Functions	102
GeometryNodeEdgePathsToCurves(GeometryNode)	104
Inherited Properties	105
Inherited Functions	105
GeometryNodeEdgePathsToSelection(GeometryNode)	107
Inherited Properties	108
Inherited Functions	108
GeometryNodeEdgesOfCorner(GeometryNode)	110
Inherited Properties	111
Inherited Functions	111
GeometryNodeEdgesOfVertex(GeometryNode)	113
Inherited Properties	114
Inherited Functions	114
GeometryNodeEdgesToFaceGroups(GeometryNode)	116
Inherited Properties	117
Inherited Functions	117
GeometryNodeExtrudeMesh(GeometryNode)	119
Inherited Properties	120
Inherited Functions	120
GeometryNodeFaceOfCorner(GeometryNode)	122
Inherited Properties	123
Inherited Functions	123
GeometryNodeFieldAtIndex(GeometryNode)	125
Inherited Properties	126
Inherited Functions	126
GeometryNodeFieldOnDomain(GeometryNode)	128
Inherited Properties	129
Inherited Functions	129

GeometryNodeFillCurve(GeometryNode)	131
Inherited Properties	132
Inherited Functions	132
GeometryNodeFilletCurve(GeometryNode)	134
Inherited Properties	135
Inherited Functions	135
GeometryNodeFlipFaces(GeometryNode)	137
Inherited Properties	138
Inherited Functions	138
GeometryNodeForeachGeometryElementInput(GeometryNode)	140
Inherited Properties	141
Inherited Functions	141
GeometryNodeForeachGeometryElementOutput(GeometryNode)	143
Inherited Properties	144
Inherited Functions	145
GeometryNodeGeometryToInstance(GeometryNode)	146
Inherited Properties	147
Inherited Functions	147
GeometryNodeGetNamedGrid(GeometryNode)	149
Inherited Properties	150
Inherited Functions	150
GeometryNodeGizmoDial(GeometryNode)	152
Inherited Properties	153
Inherited Functions	153
GeometryNodeGizmoLinear(GeometryNode)	155
Inherited Properties	156
Inherited Functions	156

[Skip to content](#)

FunctionNodeAxesToRotation(FunctionNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `FunctionNode`

class bpy.types.FunctionNodeAxesToRotation(FunctionNode)

Create a rotation from a primary and (ideally orthogonal) secondary axis

primary_axis

Axis that is aligned exactly to the provided primary direction

TYPE:

enum in ['X', 'Y', 'Z'], default 'X'

secondary_axis

Axis that is aligned as well as possible given the alignment of the primary axis

TYPE:

enum in ['X', 'Y', 'Z'], default 'X'

classmethod is_registered_node_type()

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod input_template(index)

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod output_template(index)

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `Node.poll`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`

- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.bl_rna_get_subclass_py](#)
- [NodeInternal.poll](#)
- [NodeInternal.poll_instance](#)
- [NodeInternal.update](#)
- [NodeInternal.draw_buttons](#)
- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [FunctionNode.bl_rna_get_subclass](#)
- [FunctionNode.bl_rna_get_subclass_py](#)

[Previous](#)
[FunctionNodeAlignRotationToVector\(FunctionNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
 Made with [Furo](#)

[FunctionNodeAxisAngleToRotation\(FunctionNode\)](#) [Next](#)

GeometryNodeCurveToPoints(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeCurveToPoints(GeometryNode)`

Generate a point cloud by sampling positions along curves

mode

How to generate points from the input curve

- `EVALUATED` Evaluated – Create points from the curve’s evaluated points, based on the resolution attribute for NURBS and Bézier splines.
- `COUNT` Count – Sample each spline by evenly distributing the specified number of points.
- `LENGTH` Length – Sample each spline by splitting it into segments with the specified length.

TYPE:

enum in ['EVALUATED', 'COUNT', 'LENGTH'], default 'COUNT'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:`bpy.types.Struct` subclass**classmethod** `bl_rna_get_subclass_py(id, default=None)`**PARAMETERS:****id** (*str*) – The RNA type identifier.**RETURNS:**

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`

- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Skip to content](#)

GeometryNodeCustomGroup(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeCustomGroup(GeometryNode)`

Custom Geometry Group Node for Python nodes

node_tree

TYPE:

`NodeTree`

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Skip to content](#)

GeometryNodeDeformCurvesOnSurface(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeDeformCurvesOnSurface(GeometryNode)`

Translate and rotate curves based on changes between the object's original and evaluated surface mesh

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeCustomGroup\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeDeleteGeometry\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeDeleteGeometry(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class bpy.types.GeometryNodeDeleteGeometry(GeometryNode)

Remove selected elements of a geometry

domain

Which domain to delete in

TYPE:

enum in [Attribute Domain Without Corner Items](#), default 'POINT'

mode

Which parts of the mesh component to delete

TYPE:

enum in ['ALL', 'EDGE_FACE', 'ONLY_FACE'], default 'ALL'

classmethod is_registered_node_type()

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod input_template(index)

Input socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod output_template(index)

Output socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:`bpy.types.Struct` subclass**classmethod** `bl_rna_get_subclass_py(id, default=None)`**PARAMETERS:****id** (*str*) – The RNA type identifier.**RETURNS:**

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`

- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.poll](#)
- [Node.bl_rna_get_subclass_py](#)
- [NodeInternal.poll](#)
- [NodeInternal.poll_instance](#)
- [NodeInternal.update](#)
- [NodeInternal.draw_buttons](#)
- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl_rna_get_subclass](#)
- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeDeformCurvesOnSurface\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
 Made with [Furo](#)

[GeometryNodeDistributePointsInGrid\(GeometryNode\)](#)

N

[Skip to content](#)

GeometryNodeDistributePointsInGrid(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeDistributePointsInGrid(GeometryNode)`

Generate points inside a volume grid

mode

Method to use for scattering points

- `DENSITY_RANDOM` Random – Distribute points randomly inside of the volume.
- `DENSITY_GRID` Grid – Distribute the points in a grid pattern inside of the volume.

TYPE:

enum in ['DENSITY_RANDOM', 'DENSITY_GRID'], default 'DENSITY_RANDOM'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`

- `bpy_struct.patn_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

GeometryNodeDistributePointsInVolume(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeDistributePointsInVolume(GeometryNode)`

Generate points inside a volume

mode

Method to use for scattering points

- `DENSITY_RANDOM` Random – Distribute points randomly inside of the volume.
- `DENSITY_GRID` Grid – Distribute the points in a grid pattern inside of the volume.

TYPE:

enum in ['DENSITY_RANDOM', 'DENSITY_GRID'], default 'DENSITY_RANDOM'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_to_id`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`

- `bpy_struct.patn_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)
[GeometryNodeDistributePointsInGrid\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
 Made with [Furo](#)

[GeometryNodeDistributePointsOnFaces\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeDistributePointsOnFaces(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeDistributePointsOnFaces(GeometryNode)`

Generate points spread out on the surface of a mesh

distribute_method

Method to use for scattering points

- `RANDOM` Random – Distribute points randomly on the surface.
- `POISSON` Poisson Disk – Distribute the points randomly on the surface while taking a minimum distance between points into account.

TYPE:

enum in ['RANDOM', 'POISSON'], default 'RANDOM'

use_legacy_normal

Output the normal and rotation values that have been output before the node started taking smooth normals into account

TYPE:

boolean, default False

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`

- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Skip to content](#)

GeometryNodeDualMesh(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeDualMesh(GeometryNode)`

Convert Faces into vertices and vertices into faces

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \text{inf}]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \text{inf}]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeDistributePointsOnFaces\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeDuplicateElements\(GeometryNode\)](#)

[No](#)

[Skip to content](#)

GeometryNodeDuplicateElements(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeDuplicateElements(GeometryNode)`

Generate an arbitrary number copies of each selected input element

domain

Which domain to duplicate

TYPE:

enum in ['POINT', 'EDGE', 'FACE', 'SPLINE', 'LAYER', 'INSTANCE'], default 'POINT'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`

- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`

- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)

[GeometryNodeDualMesh\(GeometryNode\)](#)

[Report issue on this page](#)

Copyright © Blender Authors

Made with [Furo](#)

[GeometryNodeEdgePathsToCurves\(GeometryNode\)](#)

Nd

[Skip to content](#)

GeometryNodeEdgePathsToCurves(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeEdgePathsToCurves(GeometryNode)`

Output curves following paths across mesh edges

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeDuplicateElements\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeEdgePathsToSelection\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeEdgePathsToSelection(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeEdgePathsToSelection(GeometryNode)`

Output a selection of edges by following paths across mesh edges

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeEdgePathsToCurves\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeEdgesOfCorner\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeEdgesOfCorner(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeEdgesOfCorner(GeometryNode)`

Retrieve the edges on both sides of a face corner

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeEdgePathsToSelection\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeEdgesOfVertex\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeEdgesOfVertex(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeEdgesOfVertex(GeometryNode)`

Retrieve the edges connected to each vertex

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeEdgesOfCorner\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeEdgesToFaceGroups\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeEdgesToFaceGroups(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeEdgesToFaceGroups(GeometryNode)`

Group faces into regions surrounded by the selected boundary edges

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeEdgesOfVertex\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeExtrudeMesh\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeExtrudeMesh(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeExtrudeMesh(GeometryNode)`

Generate new vertices, edges, or faces from selected elements and move them based on an offset while keeping them connected by their boundary

mode

TYPE:

enum in ['VERTICES', 'EDGES', 'FACES'], default 'FACES'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`

- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)
[GeometryNodeEdgesToFaceGroups\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[GeometryNodeFaceOfCorner\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeFaceOfCorner(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeFaceOfCorner(GeometryNode)`

Retrieve the face each face corner is part of

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)
- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeExtrudeMesh\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeFieldAtIndex\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeFieldAtIndex(GeometryNode)

base classes — [bpy_struct](#) , [Node](#) , [NodeInternal](#) , [GeometryNode](#)

class bpy.types.GeometryNodeFieldAtIndex(GeometryNode)

Retrieve data of other elements in the context's geometry

data_type

TYPE:

enum in [Attribute Type Items](#), default 'FLOAT'

domain

Domain the field is evaluated in

TYPE:

enum in [Attribute Domain Items](#), default 'POINT'

classmethod is_registered_node_type()

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod input_template(index)

Input socket template

PARAMETERS:

index (*int* in $[0, \text{inf}]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod output_template(index)

Output socket template

PARAMETERS:

index (*int* in $[0, \text{inf}]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`

- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.poll](#)
- [NodeInternal.poll_instance](#)
- [NodeInternal.update](#)
- [NodeInternal.draw_buttons](#)
- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl_rna_get_subclass](#)
- [GeometryNode.bl_rna_get_subclass_py](#)

[Skip to content](#)

GeometryNodeFieldOnDomain(GeometryNode)

base classes — [bpy_struct](#) , [Node](#) , [NodeInternal](#) , [GeometryNode](#)

class bpy.types.GeometryNodeFieldOnDomain(GeometryNode)

Retrieve values from a field on a different domain besides the domain from the context

data_type

TYPE:

enum in [Attribute Type Items](#), default 'FLOAT'

domain

Domain the field is evaluated in

TYPE:

enum in [Attribute Domain Items](#), default 'POINT'

classmethod is_registered_node_type()

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod input_template(index)

Input socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod output_template(index)

Output socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod bl_ma_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Skip to content](#)

GeometryNodeFillCurve(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeFillCurve(GeometryNode)`

Generate a mesh on the XY plane with faces on the inside of input curves

mode

TYPE:

enum in ['TRIANGLES', 'NGONS'], default 'TRIANGLES'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, inf]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`

- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)
[GeometryNodeFieldOnDomain\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[NodeGeometryNodeFilletCurve\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeFilletCurve(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class bpy.types.GeometryNodeFilletCurve(GeometryNode)

Round corners by generating circular arcs on each control point

mode

How to choose number of vertices on fillet

- `BEZIER` Bézier – Align Bézier handles to create circular arcs at each control point.
- `POLY` Poly – Add control points along a circular arc (handle type is vector if Bézier Spline).

TYPE:

enum in ['BEZIER', 'POLY'], default 'BEZIER'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_to_id`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`

- [bpy_struct.patn_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.poll](#)
- [NodeInternal.update](#)
- [NodeInternal.draw_buttons](#)
- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl_rna_get_subclass](#)
- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeFillCurve\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[GeometryNodeFlipFaces\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeFlipFaces(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeFlipFaces(GeometryNode)`

Reverse the order of the vertices and edges of selected faces, flipping their normal direction

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeFilletCurve\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeForeachGeometryElementInput\(GeometryNode\)](#)

[No](#)

[Skip to content](#)

GeometryNodeForeachGeometryElementInput(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeForeachGeometryElementInput(GeometryNode)`

paired_output

Zone output node that this input node is paired with

TYPE:

`Node`, (readonly)

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

pair_with_output(output_node)

Pair a zone input node with an output node.

PARAMETERS:

output_node (`GeometryNode`) – Output Node, Zone output node to pair with

RETURNS:

Result, True if pairing the node was successful

RETURN TYPE:

boolean

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`

- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Skip to content](#)

GeometryNodeForeachGeometryElementOutput(GeometryNode)

base classes — [bpy_struct](#) , [Node](#) , [NodeInternal](#) , [GeometryNode](#)

class `bpy.types.GeometryNodeForeachGeometryElementOutput(GeometryNode)`

active_generation_index

Index of the active item

TYPE:

int in [0, inf], default 0

active_input_index

Index of the active item

TYPE:

int in [0, inf], default 0

active_main_index

Index of the active item

TYPE:

int in [0, inf], default 0

domain

Geometry domain that is iterated over

TYPE:

enum in [Attribute Domain Items](#), default 'POINT'

generation_items

TYPE:

[NodeGeometryForeachGeometryElementGenerationItems](#) [bpy_prop_collection](#) of [ForeachGeometryElementGenerationItem](#) , (readonly)

input_items

TYPE:

[NodeGeometryForeachGeometryElementInputItems](#) [bpy_prop_collection](#) of [ForeachGeometryElementInputItem](#) , (readonly)

inspection_index

Iteration index that is used by inspection features like the viewer node or socket inspection

TYPE:

int in [-inf, inf], default 0

main_items

TYPE:

[NodeGeometryForeachGeometryElementMainItems](#) [bpy_prop_collection](#) of [ForeachGeometryElementMainItem](#) , (readonly)

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in $[0, inf]$*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in $[0, inf]$*) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_ma_get_subclass(id, default=None)`**PARAMETERS:**

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`**PARAMETERS:**

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`

- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

GeometryNodeGeometryToInstance(GeometryNode)

base classes — `bpy_struct`, `Node`, `NodeInternal`, `GeometryNode`

class `bpy.types.GeometryNodeGeometryToInstance(GeometryNode)`

Convert each input geometry into an instance, which can be much faster than the Join Geometry node when the inputs are large

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

`NodeInternalSocketTemplate`

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`
- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`

- [Node.poll](#)

- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)
[GeometryNodeForeachGeometryElementOutput\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeGetNamedGrid\(GeometryNode\)](#)

[No](#)

[Skip to content](#)

GeometryNodeGetNamedGrid(GeometryNode)

base classes — [bpy_struct](#) , [Node](#) , [NodeInternal](#) , [GeometryNode](#)

class `bpy.types.GeometryNodeGetNamedGrid(GeometryNode)`

Get volume grid from a volume geometry with the specified name

data_type

Type of grid data

TYPE:

enum in [Node Socket Data Type Items](#), default 'FLOAT'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`

- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.poll](#)

- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl_rna_get_subclass](#)
- [GeometryNode.bl_rna_get_subclass_py](#)

[Previous](#)

[GeometryNodeGeometryToInstance\(GeometryNode\)](#)

[Report issue on this page](#)

Copyright © Blender Authors

Made with [Furo](#)

[GeometryNodeGizmoDial\(GeometryNode\)](#)

[Node](#)

[Skip to content](#)

GeometryNodeGizmoDial(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class `bpy.types.GeometryNodeGizmoDial(GeometryNode)`

Show a dial gizmo in the viewport for a value

color_id

TYPE:

enum in [Geometry Nodes Gizmo Color Items](#), default 'PRIMARY'

classmethod `is_registered_node_type()`

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod `input_template(index)`

Input socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `output_template(index)`

Output socket template

PARAMETERS:

index (*int* in $[0, \infty]$) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`
- `NodeInternal.update`
- `NodeInternal.draw_buttons`
- `NodeInternal.draw_buttons_ext`
- `NodeInternal.bl_rna_get_subclass`

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Node.socket_value_update`
- `Node.is_registered_node_type`
- `Node.poll`

- `NodeInternal.bl_rna_get_subclass_py`
- `GeometryNode.poll`
- `GeometryNode.bl_rna_get_subclass`
- `GeometryNode.bl_rna_get_subclass_py`

[Previous](#)
[GeometryNodeGetNamedGrid\(GeometryNode\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[GeometryNodeGizmoLinear\(GeometryNode\)](#)

[Skip to content](#)

GeometryNodeGizmoLinear(GeometryNode)

base classes — [bpy_struct](#), [Node](#), [NodeInternal](#), [GeometryNode](#)

class bpy.types.GeometryNodeGizmoLinear(GeometryNode)

Show a linear gizmo in the viewport for a value

color_id

TYPE:

enum in [Geometry Nodes Gizmo Color Items](#), default 'PRIMARY'

draw_style

TYPE:

enum in [Geometry Nodes Linear Gizmo Draw Style Items](#), default 'ARROW'

classmethod is_registered_node_type()

True if a registered node type

RETURNS:

Result

RETURN TYPE:

boolean

classmethod input_template(index)

Input socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod output_template(index)

Output socket template

PARAMETERS:

index (*int in [0, inf]*) – Index

RETURNS:

result

RETURN TYPE:

[NodeInternalSocketTemplate](#)

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Node.type`
- `Node.location`
- `Node.location_absolute`
- `Node.width`
- `Node.height`
- `Node.dimensions`
- `Node.name`
- `Node.label`
- `Node.inputs`
- `Node.outputs`
- `Node.internal_links`
- `Node.parent`
- `Node.warning_propagation`
- `Node.use_custom_color`
- `Node.color`
- `Node.color_tag`
- `Node.select`
- `Node.show_options`
- `Node.show_preview`
- `Node.hide`
- `Node.mute`
- `Node.show_texture`
- `Node.bl_idname`
- `Node.bl_label`
- `Node.bl_description`
- `Node.bl_icon`
- `Node.bl_static_type`
- `Node.bl_width_default`
- `Node.bl_width_min`
- `Node.bl_width_max`
- `Node.bl_height_default`
- `Node.bl_height_min`
- `Node.bl_height_max`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `Node.poll_instance`
- `Node.update`
- `Node.insert_link`
- `Node.init`
- `Node.copy`
- `Node.free`
- `Node.draw_buttons`
- `Node.draw_buttons_ext`
- `Node.draw_label`
- `Node.debug_zone_body_lazy_function_graph`
- `Node.debug_zone_lazy_function_graph`
- `Node.poll`
- `Node.bl_rna_get_subclass`
- `Node.bl_rna_get_subclass_py`
- `NodeInternal.poll`
- `NodeInternal.poll_instance`

- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)
- [bpy_struct.property_unset](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Node.socket_value_update](#)
- [Node.is_registered_node_type](#)
- [Node.poll](#)
- [NodeInternal.update](#)
- [NodeInternal.draw_buttons](#)
- [NodeInternal.draw_buttons_ext](#)
- [NodeInternal.bl_rna_get_subclass](#)
- [NodeInternal.bl_rna_get_subclass_py](#)
- [GeometryNode.poll](#)
- [GeometryNode.bl_rna_get_subclass](#)
- [GeometryNode.bl_rna_get_subclass_py](#)