

[Skip to content](#)

StripModifiers(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.StripModifiers(bpy_struct)`

Collection of strip modifiers

new(name, type)

Add a new modifier

PARAMETERS:

- **name** (*string, (never None)*) – New name for the modifier
- **type** (enum in [Strip Modifier Type Items](#)) – Modifier type to add

RETURNS:

Newly created modifier

RETURN TYPE:

[StripModifier](#)

remove(modifier)

Remove an existing modifier from the sequence

PARAMETERS:

modifier ([StripModifier](#), (never None)) – Modifier to remove

clear()

Remove all modifiers from the sequence

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Strip.modifiers`

[Previous](#)
[StripModifier\(bpy_struct\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
Made with [Furo](#)

[Next](#)
[StripProxy\(bpy_struct\)](#)