RetimingKey(bpy_struct)

base class — `bpy_struct`

class bpy.types.**RetimingKey(bpy_struct)**

> Key mapped to particular frame that can be moved to change playback speed

> **timeline_frame**
>
> > Position of retiming key in timeline
> >
> > **TYPE:**
> >
> > > int in [-inf, inf], default 0

> **remove()**
>
> > Remove retiming key

> **classmethod bl_rna_get_subclass(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The RNA type or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > `bpy.types.Struct` subclass

> **classmethod bl_rna_get_subclass_py(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The class or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`

- bpy_struct.is_property_set
- bpy_struct.values

References

- ImageStrip.retiming_keys
- MovieStrip.retiming_keys
- RetimingKeys.add
- SceneStrip.retiming_keys
- SoundStrip.retiming_keys

Report issue on this page