Skip to content

Laplacian Smooth Modifier (Modifier)

```
base classes — bpy_struct, Modifier
class bpy.types.LaplacianSmoothModifier(Modifier)
    Smoothing effect modifier
     invert_vertex_group
         Invert vertex group influence
         TYPE:
              boolean, default False
     iterations
         TYPE:
              int in [0, 32767], default 1
     lambda\_border
         Lambda factor in border
         TYPE:
              float in [-inf, inf], default 0.01
     lambda_factor
         Smooth effect factor
         TYPE:
              float in [-inf, inf], default 0.01
     use_normalized
         Improve and stabilize the enhanced shape
         TYPE:
              boolean, default True
     use_volume_preserve
         Apply volume preservation after smooth
         TYPE:
              boolean, default True
     use_x
         Smooth object along X axis
         TYPE:
              boolean, default True
     use_y
         Smooth object along Y axis
         TYPE:
              boolean, default True
```

Smooth object along Z axis

use_z

```
TYPE:
        boolean, default True
vertex group
   Name of Vertex Group which determines influence of modifier per point
    TYPE:
        string, default ", (never None)
classmethod bl_rna_get_subclass(id, default=None)
    PARAMETERS:
        id (str) – The RNA type identifier.
   RETURNS:
        The RNA type or default when not found.
    RETURN TYPE:
        bpy.types.Struct subclass
classmethod bl_rna_get_subclass_py(id, default=None)
    PARAMETERS:
        id(str) – The RNA type identifier.
    RETURNS:
        The class or default when not found.
    RETURN TYPE:
        type
```

Inherited Properties

• bpy_struct.id_data Modifier.show_expanded • Modifier.name • Modifier.is active Modifier.type • Modifier.use_pin_to_last • Modifier.show_viewport • Modifier.is_override_data Modifier.show render
 Modifier.use apply on spline • Modifier.show in editmode • Modifier.execution time Modifier.show_on_cage Modifier.persistent uid

Inherited Functions

- bpy_struct.as_pointer • bpy struct.driver add • bpy_struct.driver_remove • bpy struct.get • bpy struct.id properties clear • bpy struct.id properties ensure • bpy struct.id properties ui • bpy struct.is property hidden • bpy struct.is property_overridable_library • bpy_struct.type_recast • bpy struct.is property readonly • bpy_struct.is_property_set
- bpy_struct.keyframe_delete • bpy struct.keyframe insert • bpy_struct.keys • bpy struct.path from id • bpy struct.path resolve • bpy struct.pop
 - bpy_struct.property_overridable_library_set
 - bpy struct.property unset

 - bpy struct.values
 - Modifier.bl_rna_get_subclass

• bpy_struct.items

• Modifier.bl_rna_get_subclass_py

Previous LaplacianDeformModifier(Modifier) Report issue on this page Copyright © Blender Authors Made with Furo No Lattice(I