VIEWLAYER UL aov(UIList)

```
base classes — bpy_struct, UIList
class bpy.types.VIEWLAYER UL aov(UIList)
    draw item( context, layout, data, item, icon, active data, active propname)
    classmethod bl rna get subclass(id, default=None)
        PARAMETERS:
             id(str) – The RNA type identifier.
        RETURNS:
             The RNA type or default when not found.
        RETURN TYPE:
             bpy.types.Struct subclass
    classmethod bl_rna_get_subclass_py(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The class or default when not found.
        RETURN TYPE:
             type
```

Inherited Properties

- bpy struct.id data
- UIList.bl idname
- UIList.list_id
- UIList.layout_type
- UIList.use_filter_show
- UIList.filter name
- UIList.use filter invert
- UIList.use_filter_sort_alpha
- UIList.use_filter_sort_reverse
- UIList.use filter sort lock
- UIList.bitflag_filter_item

Inherited Functions

- bpy_struct.as_pointer • bpy struct.driver add
- bpy struct.driver remove
- bpy_struct.get
- bpy struct.id properties clear
- bpy_struct.id_properties_ensure
- bpy struct.id properties ui
- bpy struct.is property hidden
- bpy_struct.is_property_overridable_library
- bpy struct.is property readonly
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.path_resolve
- bpy struct.pop
- bpy struct.property overridable library set
- bpy struct.property unset
- bpy struct.type recast
- bpy struct.values
- UIList.draw item
- UIList.draw filter
- UIList.filter_items
- UIList.append
- UIList.is extended
- UIList.prepend

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- UIList.remove
- UIList.bl_rna_get_subclass
- UIList.bl_rna_get_subclass_py

Previous VIEW3D_FH_vdb_volume(FileHandler) Report issue on this page

Copyright © Blender Authors Made with Furo

VIEWLAYER_UL_linesets(UILi