

[Skip to content](#)

# StripElement(bpy\_struct)

base class — `bpy_struct`

**class** `bpy.types.StripElement(bpy_struct)`

Sequence strip data for a single frame

## **filename**

Name of the source file

## **TYPE:**

string, default ‘’, (never None)

## **orig\_fps**

Original frames per second

## **TYPE:**

float in [-inf, inf], default 0.0, (readonly)

## **orig\_height**

Original image height

## **TYPE:**

int in [-inf, inf], default 0, (readonly)

## **orig\_width**

Original image width

## **TYPE:**

int in [-inf, inf], default 0, (readonly)

**classmethod** `bl_rna_get_subclass(id, default=None)`

## **PARAMETERS:**

**id** (*str*) – The RNA type identifier.

## **RETURNS:**

The RNA type or default when not found.

## **RETURN TYPE:**

`bpy.types.Struct` subclass

**classmethod** `bl_rna_get_subclass_py(id, default=None)`

## **PARAMETERS:**

**id** (*str*) – The RNA type identifier.

## **RETURNS:**

The class or default when not found.

## **RETURN TYPE:**

type

## Inherited Properties

- `bpy_struct.id_data`

# Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

# References

- `ImageStrip.elements` • `Strip.strip_elem_from_frame`
- `MovieStrip.elements` • `StripElements.append`