

[Skip to content](#)

PaintModeSettings(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.PaintModeSettings(bpy_struct)`

Properties of paint mode

canvas_image

Image used as painting target

TYPE:

[Image](#)

canvas_source

Source to select canvas from

TYPE:

enum in ['COLOR_ATTRIBUTE', 'MATERIAL', 'IMAGE'], default 'MATERIAL'

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.id_properties_ui](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)
- [bpy_struct.property_overridable_library_set](#)

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ToolSettings.paint_mode`