

base classes — `bpy_struct`, `ID`

class `bpy.types.Mask(ID)`

Mask data-block defining mask for compositing

active_layer_index

Index of active layer in list of all mask's layers

TYPE:

int in `[-inf, inf]`, default 0

animation_data

Animation data for this data-block

TYPE:

`AnimData`, (readonly)

frame_end

Final frame of the mask (used for sequencer)

TYPE:

int in `[0, 1048574]`, default 0

frame_start

First frame of the mask (used for sequencer)

TYPE:

int in `[0, 1048574]`, default 0

layers

Collection of layers which defines this mask

TYPE:

`MaskLayers` `bpy_prop_collection` of `MaskLayer`, (readonly)

classmethod `bl_ma_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_ma_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.name_full`
- `ID.id_type`
- `ID.session_uid`
- `ID.is_evaluated`
- `ID.original`
- `ID.users`
- `ID.use_fake_user`
- `ID.use_extra_user`
- `ID.is_embedded_data`
- `ID.is_missing`
- `ID.is_runtime_data`
- `ID.is_editable`
- `ID.tag`
- `ID.is_library_indirect`
- `ID.library`
- `ID.library_weak_reference`
- `ID.asset_data`
- `ID.override_library`
- `ID.preview`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.rename`
- `ID.evaluated_get`
- `ID.copy`
- `ID.asset_mark`
- `ID.asset_clear`
- `ID.asset_generate_preview`
- `ID.override_create`
- `ID.override_hierarchy_create`
- `ID.user_clear`
- `ID.user_remap`
- `ID.make_local`
- `ID.user_of_id`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`
- `ID.preview_ensure`
- `ID.bl_rna_get_subclass`
- `ID.bl_rna_get_subclass_py`

References

- `bpy.context.edit_mask`
- `BlendData.masks`
- `BlendDataMasks.new`
- `BlendDataMasks.remove`
- `CompositorNodeMask.mask`
- `MaskStrip.mask`
- `SpaceClipEditor.mask`
- `SpaceImageEditor.mask`
- `StripModifier.input_mask_id`
- `StripsMeta.new_mask`
- `StripsTopLevel.new_mask`

