

[Skip to content](#)

Math Types & Utilities (mathutils)

This module provides access to math operations.

Note

Classes, methods and attributes that accept vectors also accept other numeric sequences, such as tuples, lists.

The `mathutils` module provides the following classes:

- `Color`,
- `Euler`,
- `Matrix`,
- `Quaternion`,
- `Vector`,

SUBMODULES

[Geometry Utilities \(mathutils.geometry\)](#)

[BVHTree Utilities \(mathutils.bvhtree\)](#)

[KDTree Utilities \(mathutils.kdtree\)](#)

[Interpolation Utilities \(mathutils.interpolate\)](#)

[Noise Utilities \(mathutils.noise\)](#)

```
import mathutils
from math import radians

vec = mathutils.Vector((1.0, 2.0, 3.0))

mat_rot = mathutils.Matrix.Rotation(radians(90.0), 4, 'X')
mat_trans = mathutils.Matrix.Translation(vec)

mat = mat_trans @ mat_rot
mat.invert()

mat3 = mat.to_3x3()
quat1 = mat.to_quaternion()
quat2 = mat3.to_quaternion()

quat_diff = quat1.rotation_difference(quat2)

print(quat_diff.angle)
```

class mathutils.Color(rgb)

This object gives access to Colors in Blender.

Most colors returned by Blender APIs are in scene linear color space, as defined by the OpenColorIO configuration. The notable exception is user interface theming colors, which are in sRGB color space.

PARAMETERS:

rgb (*Sequence[float]*) – (red, green, blue) color values where (0, 0, 0) is black & (1, 1, 1) is white.

```
import mathutils

# color values are represented as RGB values from 0 - 1, this is blue
```

```

col = mathutils.Color((0.0, 0.0, 1.0))

# as well as r/g/b attribute access you can adjust them by h/s/v
col.s *= 0.5

# you can access its components by attribute or index
print("Color R:", col.r)
print("Color G:", col[1])
print("Color B:", col[-1])
print("Color HSV: {:.2f}, {:.2f}, {:.2f}".format(*col))

# components of an existing color can be set
col[:] = 0.0, 0.5, 1.0

# components of an existing color can use slice notation to get a tuple
print("Values: {:.f}, {:.f}, {:.f}".format(*col))

# colors can be added and subtracted
col += mathutils.Color((0.25, 0.0, 0.0))

# Color can be multiplied, in this example color is scaled to 0-255
# can printed as integers
print("Color: {:d}, {:d}, {:d}".format(*(int(c) for c in (col * 255.0))))

# This example prints the color as hexadecimal
print("Hexadecimal: {:02x}{:02x}{:02x}".format(int(col.r * 255), int(col.g * 255), int(

```

copy()

Returns a copy of this color.

RETURNS:

A copy of the color.

RETURN TYPE:

Color

Note

use this to get a copy of a wrapped color with no reference to the original data.

freeze()

Make this object immutable.

After this the object can be hashed, used in dictionaries & sets.

RETURNS:

An instance of this object.

from_aces_to_scene_linear()

Convert from ACES2065-1 linear to scene linear color space.

RETURNS:

A color in scene linear color space.

RETURN TYPE:

Color

from_rec709_linear_to_scene_linear()

Convert from Rec.709 linear color space to scene linear color space.

RETURNS:

A color in scene linear color space.

RETURN TYPE:

`Color`

from_scene_linear_to_aces()

Convert from scene linear to ACES2065-1 linear color space.

RETURNS:

A color in ACES2065-1 linear color space.

RETURN TYPE:

`Color`

from_scene_linear_to_rec709_linear()

Convert from scene linear to Rec.709 linear color space.

RETURNS:

A color in Rec.709 linear color space.

RETURN TYPE:

`Color`

from_scene_linear_to_srgb()

Convert from scene linear to sRGB color space.

RETURNS:

A color in sRGB color space.

RETURN TYPE:

`Color`

from_scene_linear_to_xyz_d65()

Convert from scene linear to CIE XYZ (Illuminant D65) color space.

RETURNS:

A color in XYZ color space.

RETURN TYPE:

`Color`

from_srgb_to_scene_linear()

Convert from sRGB to scene linear color space.

RETURNS:

A color in scene linear color space.

RETURN TYPE:

`Color`

from_xyz_d65_to_scene_linear()

Convert from CIE XYZ (Illuminant D65) to scene linear color space.

RETURNS:

A color in scene linear color space.

RETURN TYPE:

Color

b

Blue color channel.

TYPE:

float

g

Green color channel.

TYPE:

float

h

HSV Hue component in [0, 1].

TYPE:

float

hsv

HSV Values in [0, 1].

TYPE:

float triplet

is_frozen

True when this object has been frozen (read-only).

TYPE:

bool

is_valid

True when the owner of this data is valid.

TYPE:

bool

is_wrapped

True when this object wraps external data (read-only).

TYPE:

bool

owner

The item this is wrapping or None (read-only).

r

Red color channel.

TYPE:

float

s

HSV Saturation component in [0, 1].

TYPE:

float

v

HSV Value component in [0, 1].

TYPE:

float

class mathutils.Euler(**angles**, **order**='XYZ')

This object gives access to Eulers in Blender.

See also

[Euler angles](#) on Wikipedia.

PARAMETERS:

- **angles** (*Sequence[float]*) – (X, Y, Z) angles in radians.
- **order** (*str*) – Optional order of the angles, a permutation of XYZ .

```
import mathutils
import math

# create a new euler with default axis rotation order
eul = mathutils.Euler((0.0, math.radians(45.0), 0.0), 'XYZ')

# rotate the euler
eul.rotate_axis('Z', math.radians(10.0))

# you can access its components by attribute or index
print("Euler X", eul.x)
print("Euler Y", eul[1])
print("Euler Z", eul[-1])

# components of an existing euler can be set
eul[:] = 1.0, 2.0, 3.0

# components of an existing euler can use slice notation to get a tuple
print("Values: {:f}, {:f}, {:f}".format(*eul))

# the order can be set at any time too
eul.order = 'ZYX'

# eulers can be used to rotate vectors
vec = mathutils.Vector((0.0, 0.0, 1.0))
vec.rotate(eul)

# often its useful to convert the euler into a matrix so it can be used as
# transformations with more flexibility
mat_rot = eul.to_matrix()
mat_loc = mathutils.Matrix.Translation((2.0, 3.0, 4.0))
mat = mat_loc @ mat_rot.to_4x4()
```

copy()

Returns a copy of this euler.

RETURNS:

RETURNS:

A copy of the euler.

RETURN TYPE:

`Euler`

Note

use this to get a copy of a wrapped euler with no reference to the original data.

freeze()

Make this object immutable.

After this the object can be hashed, used in dictionaries & sets.

RETURNS:

An instance of this object.

make_compatible(other)

Make this euler compatible with another, so interpolating between them works as intended.

Note

the rotation order is not taken into account for this function.

rotate(other)

Rotates the euler by another mathutils value.

PARAMETERS:

other (`Euler` | `Quaternion` | `Matrix`) – rotation component of mathutils value

rotate_axis(axis, angle)

Rotates the euler a certain amount and returning a unique euler rotation (no 720 degree pitches).

PARAMETERS:

- **axis** (*str*) – single character in ['X', 'Y', 'Z'].
- **angle** (*float*) – angle in radians.

to_matrix()

Return a matrix representation of the euler.

RETURNS:

A 3x3 rotation matrix representation of the euler.

RETURN TYPE:

`Matrix`

to_quaternion()

Return a quaternion representation of the euler.

RETURNS:

Quaternion representation of the euler.

RETURN TYPE:

`Quaternion`

zero()

Set all values to zero.

is_frozen

True when this object has been frozen (read-only).

TYPE:

bool

is_valid

True when the owner of this data is valid.

TYPE:

bool

is_wrapped

True when this object wraps external data (read-only).

TYPE:

bool

order

Euler rotation order.

TYPE:

str in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX']

owner

The item this is wrapping or None (read-only).

x

Euler axis angle in radians.

TYPE:

float

y

Euler axis angle in radians.

TYPE:

float

z

Euler axis angle in radians.

TYPE:

float

class mathutils.Matrix([rows])

This object gives access to Matrices in Blender, supporting square and rectangular matrices from 2x2 up to 4x4.

PARAMETERS:

rows (*Sequence[Sequence[float]]*) – Sequence of rows. When omitted, a 4x4 identity matrix is constructed.

```
import mathutils
import math

# Create a location matrix.
mat_loc = mathutils.Matrix.Translation((2.0, 3.0, 4.0))

# Create an identity matrix.
```

```

mat_sca = mathutils.Matrix.Scale(0.5, 4, (0.0, 0.0, 1.0))

# Create a rotation matrix.
mat_rot = mathutils.Matrix.Rotation(math.radians(45.0), 4, 'X')

# Combine transformations.
mat_out = mat_loc @ mat_rot @ mat_sca
print(mat_out)

# Extract components back out of the matrix as two vectors and a quaternion.
loc, rot, sca = mat_out.decompose()
print(loc, rot, sca)

# Recombine extracted components.
mat_out2 = mathutils.Matrix.LocRotScale(loc, rot, sca)
print(mat_out2)

# It can also be useful to access components of a matrix directly.
mat = mathutils.Matrix()
mat[0][0], mat[1][0], mat[2][0] = 0.0, 1.0, 2.0

mat[0][0:3] = 0.0, 1.0, 2.0

# Each item in a matrix is a vector so vector utility functions can be used.
mat[0].xyz = 0.0, 1.0, 2.0

```

classmethod Diagonal(vector)

Create a diagonal (scaling) matrix using the values from the vector.

PARAMETERS:

vector ([Vector](#)) – The vector of values for the diagonal.

RETURNS:

A diagonal matrix.

RETURN TYPE:

[Matrix](#)

classmethod Identity(size)

Create an identity matrix.

PARAMETERS:

size (*int*) – The size of the identity matrix to construct [2, 4].

RETURNS:

A new identity matrix.

RETURN TYPE:

[Matrix](#)

classmethod LocRotScale(location, rotation, scale)

Create a matrix combining translation, rotation and scale, acting as the inverse of the `decompose()` method.

Any of the inputs may be replaced with `None` if not needed.

PARAMETERS:

- **location** ([Vector](#) | `None`) – The translation component.
- **rotation** ([Matrix](#) | [Quaternion](#) | [Euler](#) | `None`) – The rotation component as a 3x3 matrix, quaternion, euler or `None` for no rotation.

rotation.

- **scale** ([Vector](#) | None) – The scale component.

RETURNS:

Combined transformation as a 4x4 matrix.

RETURN TYPE:

[Matrix](#)

```
# Compute local object transformation matrix:
if obj.rotation_mode == 'QUATERNION':
    matrix = mathutils.Matrix.LocRotScale(obj.location, obj.rotation_quaternion, obj
else:
    matrix = mathutils.Matrix.LocRotScale(obj.location, obj.rotation_euler, obj.scal
```

classmethod OrthoProjection(axis, size)

Create a matrix to represent an orthographic projection.

PARAMETERS:

- **axis** (str | [Vector](#)) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix. Or a vector for an arbitrary axis
- **size** (int) – The size of the projection matrix to construct [2, 4].

RETURNS:

A new projection matrix.

RETURN TYPE:

[Matrix](#)

classmethod Rotation(angle, size, axis)

Create a matrix representing a rotation.

PARAMETERS:

- **angle** (float) – The angle of rotation desired, in radians.
- **size** (int) – The size of the rotation matrix to construct [2, 4].
- **axis** (str | [Vector](#)) – a string in ['X', 'Y', 'Z'] or a 3D Vector Object (optional when size is 2).

RETURNS:

A new rotation matrix.

RETURN TYPE:

[Matrix](#)

classmethod Scale(factor, size, axis)

Create a matrix representing a scaling.

PARAMETERS:

- **factor** (float) – The factor of scaling to apply.
- **size** (int) – The size of the scale matrix to construct [2, 4].
- **axis** ([Vector](#)) – Direction to influence scale. (optional).

RETURNS:

A new scale matrix.

RETURN TYPE:

[Matrix](#)

classmethod Shear(plane, size, factor)

Create a matrix to represent an shear transformation.

PARAMETERS:

- **plane** (*str*) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix only.
- **size** (*int*) – The size of the shear matrix to construct [2, 4].
- **factor** (*float* | *Sequence[float]*) – The factor of shear to apply. For a 2 *size* matrix use a single float. For a 3 or 4 *size* matrix pass a pa of floats corresponding with the *plane* axis.

RETURNS:

A new shear matrix.

RETURN TYPE:

[Matrix](#)

classmethod Translation(vector)

Create a matrix representing a translation.

PARAMETERS:

vector ([Vector](#)) – The translation vector.

RETURNS:

An identity matrix with a translation.

RETURN TYPE:

[Matrix](#)

adjugate()

Set the matrix to its adjugate.

RAISES:

ValueError – if the matrix cannot be adjugate.

See also

[Adjugate matrix](#) on Wikipedia.

adjugated()

Return an adjugated copy of the matrix.

RETURNS:

the adjugated matrix.

RETURN TYPE:

[Matrix](#)

RAISES:

ValueError – if the matrix cannot be adjugated

copy()

Returns a copy of this matrix.

RETURNS:

an instance of itself

RETURN TYPE:

[Matrix](#)

decompose()

Return the translation, rotation, and scale components of this matrix.

RETURNS:

RETURNS:

Tuple of translation, rotation, and scale.

RETURN TYPE:

tuple[[Vector](#), [Quaternion](#), [Vector](#)]

determinant()

Return the determinant of a matrix.

RETURNS:

Return the determinant of a matrix.

RETURN TYPE:

float

See also

[Determinant](#) on Wikipedia.

freeze()

Make this object immutable.

After this the object can be hashed, used in dictionaries & sets.

RETURNS:

An instance of this object.

identity()

Set the matrix to the identity matrix.

Note

An object with a location and rotation of zero, and a scale of one will have an identity matrix.

See also

[Identity matrix](#) on Wikipedia.

invert(fallback=None)

Set the matrix to its inverse.

PARAMETERS:

fallback ([Matrix](#)) – Set the matrix to this value when the inverse cannot be calculated (instead of raising a `ValueError` exception).

See also

[Inverse matrix](#) on Wikipedia.

invert_safe()

Set the matrix to its inverse, will never error. If degenerated (e.g. zero scale on an axis), add some epsilon to its diagonal, to get an invertible one. If tweaked matrix is still degenerated, set to the identity matrix instead.

See also

[Inverse Matrix](#) on Wikipedia.

inverted(fallback=None)

Return an inverted copy of the matrix.

PARAMETERS:

PARAMETERS:

fallback (*Any*) – return this when the inverse can't be calculated (instead of raising a `ValueError`).

RETURNS:

The inverted matrix or fallback when given.

RETURN TYPE:

`Matrix` | `Any`

inverted_safe()

Return an inverted copy of the matrix, will never error. If degenerated (e.g. zero scale on an axis), add some epsilon to its diagonal, to get an invertible one. If tweaked matrix is still degenerated, return the identity matrix instead.

RETURNS:

the inverted matrix.

RETURN TYPE:

`Matrix`

lerp(other, factor)

Returns the interpolation of two matrices. Uses polar decomposition, see “Matrix Animation and Polar Decomposition”, Shoemake and Duff, 1992.

PARAMETERS:

- **other** (`Matrix`) – value to interpolate with.
- **factor** (*float*) – The interpolation value in $[0.0, 1.0]$.

RETURNS:

The interpolated matrix.

RETURN TYPE:

`Matrix`

normalize()

Normalize each of the matrix columns.

Note

for 4x4 matrices, the 4th column (translation) is left untouched.

normalized()

Return a column normalized matrix

RETURNS:

a column normalized matrix

RETURN TYPE:

`Matrix`

Note

for 4x4 matrices, the 4th column (translation) is left untouched.

resize_4x4()

Resize the matrix to 4x4.

rotate(other)

Rotates the matrix by another `mathutils` value.

PARAMETERS:

other ([Euler](#) | [Quaternion](#) | [Matrix](#)) – rotation component of mathutils value

Note

If any of the columns are not unit length this may not have desired results.

to_2x2()

Return a 2x2 copy of this matrix.

RETURNS:

a new matrix.

RETURN TYPE:

[Matrix](#)

to_3x3()

Return a 3x3 copy of this matrix.

RETURNS:

a new matrix.

RETURN TYPE:

[Matrix](#)

to_4x4()

Return a 4x4 copy of this matrix.

RETURNS:

a new matrix.

RETURN TYPE:

[Matrix](#)

to_euler(order, euler_compat)

Return an Euler representation of the rotation matrix (3x3 or 4x4 matrix only).

PARAMETERS:

- **order** (*str*) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- **euler_compat** ([Euler](#)) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

RETURNS:

Euler representation of the matrix.

RETURN TYPE:

[Euler](#)

to_quaternion()

Return a quaternion representation of the rotation matrix.

RETURNS:

Quaternion representation of the rotation matrix.

RETURN TYPE:

[Quaternion](#)

to_scale()

Return the scale part of a 3x3 or 4x4 matrix.

RETURNS:

Return the scale of a matrix.

RETURN TYPE:

`Vector`

Note

This method does not return a negative scale on any axis because it is not possible to obtain this data from the matrix alone.

to_translation()

Return the translation part of a 4 row matrix.

RETURNS:

Return the translation of a matrix.

RETURN TYPE:

`Vector`

transpose()

Set the matrix to its transpose.

See also

[Transpose](#) on Wikipedia.

transposed()

Return a new, transposed matrix.

RETURNS:

a transposed matrix

RETURN TYPE:

`Matrix`

zero()

Set all the matrix values to zero.

col

Access the matrix by columns, 3x3 and 4x4 only, (read-only).

TYPE:

Matrix Access

is_frozen

True when this object has been frozen (read-only).

TYPE:

bool

is_identity

True if this is an identity matrix (read-only).

TYPE:

bool

is_negative

True if this matrix results in a negative scale, 3x3 and 4x4 only, (read-only).

TYPE:

bool

0001

is_orthogonal

True if this matrix is orthogonal, 3x3 and 4x4 only, (read-only).

TYPE:

bool

is_orthogonal_axis_vectors

True if this matrix has got orthogonal axis vectors, 3x3 and 4x4 only, (read-only).

TYPE:

bool

is_valid

True when the owner of this data is valid.

TYPE:

bool

is_wrapped

True when this object wraps external data (read-only).

TYPE:

bool

median_scale

The average scale applied to each axis (read-only).

TYPE:

float

owner

The item this is wrapping or None (read-only).

row

Access the matrix by rows (default), (read-only).

TYPE:

Matrix Access

translation

The translation component of the matrix.

TYPE:

[Vector](#)

class mathutils.Quaternion([seq[, angle]])

This object gives access to Quaternions in Blender.

PARAMETERS:

- **seq** ([Vector](#)) – size 3 or 4
- **angle** (*float*) – rotation angle, in radians

The constructor takes arguments in various forms:

(), *no args*

Create an identity quaternion

(wxyz)

Create a quaternion from a (w, x, y, z) vector.

(exponential_map)

Create a quaternion from a 3d exponential map vector.

See also

`to_exponential_map()`

(axis, angle)

Create a quaternion representing a rotation of *angle* radians over *axis*.

See also

`to_axis_angle()`

```
import mathutils
import math

# a new rotation 90 degrees about the Y axis
quat_a = mathutils.Quaternion((0.7071068, 0.0, 0.7071068, 0.0))

# passing values to Quaternion's directly can be confusing so axis, angle
# is supported for initializing too
quat_b = mathutils.Quaternion((0.0, 1.0, 0.0), math.radians(90.0))

print("Check quaternions match", quat_a == quat_b)

# like matrices, quaternions can be multiplied to accumulate rotational values
quat_a = mathutils.Quaternion((0.0, 1.0, 0.0), math.radians(90.0))
quat_b = mathutils.Quaternion((0.0, 0.0, 1.0), math.radians(45.0))
quat_out = quat_a @ quat_b

# print the quat, euler degrees for mere mortals and (axis, angle)
print("Final Rotation:")
print(quat_out)
print("{:.2f}, {:.2f}, {:.2f}".format(*math.degrees(a) for a in quat_out.to_euler()))
print("{:.2f}, {:.2f}, {:.2f}, {:.2f}".format(*quat_out.axis, math.degrees(quat_out.angle)))

# multiple rotations can be interpolated using the exponential map
quat_c = mathutils.Quaternion((1.0, 0.0, 0.0), math.radians(15.0))
exp_avg = (quat_a.to_exponential_map() +
            quat_b.to_exponential_map() +
            quat_c.to_exponential_map()) / 3.0
quat_avg = mathutils.Quaternion(exp_avg)
print("Average rotation:")
print(quat_avg)
```

conjugate()

Set the quaternion to its conjugate (negate x, y, z).

conjugated()

Return a new conjugated quaternion.

RETURNS:

Quaternion

a new quaternion.

RETURN TYPE:

[Quaternion](#)

copy()

Returns a copy of this quaternion.

RETURNS:

A copy of the quaternion.

RETURN TYPE:

[Quaternion](#)

Note

use this to get a copy of a wrapped quaternion with no reference to the original data.

cross(other)

Return the cross product of this quaternion and another.

PARAMETERS:

other ([Quaternion](#)) – The other quaternion to perform the cross product with.

RETURNS:

The cross product.

RETURN TYPE:

[Quaternion](#)

dot(other)

Return the dot product of this quaternion and another.

PARAMETERS:

other ([Quaternion](#)) – The other quaternion to perform the dot product with.

RETURNS:

The dot product.

RETURN TYPE:

float

freeze()

Make this object immutable.

After this the object can be hashed, used in dictionaries & sets.

RETURNS:

An instance of this object.

identity()

Set the quaternion to an identity quaternion.

invert()

Set the quaternion to its inverse.

inverted()

Return a new, inverted quaternion.

RETURNS:

the inverted value.

RETURN TYPE:

`Quaternion`

make_compatible(other)

Make this quaternion compatible with another, so interpolating between them works as intended.

negate()

Set the quaternion to its negative.

normalize()

Normalize the quaternion.

normalized()

Return a new normalized quaternion.

RETURNS:

a normalized copy.

RETURN TYPE:

`Quaternion`

rotate(other)

Rotates the quaternion by another mathutils value.

PARAMETERS:

other (`Euler` | `Quaternion` | `Matrix`) – rotation component of mathutils value

rotation_difference(other)

Returns a quaternion representing the rotational difference.

PARAMETERS:

other (`Quaternion`) – second quaternion.

RETURNS:

the rotational difference between the two quat rotations.

RETURN TYPE:

`Quaternion`

slerp(other, factor)

Returns the interpolation of two quaternions.

PARAMETERS:

- **other** (`Quaternion`) – value to interpolate with.
- **factor** (*float*) – The interpolation value in [0.0, 1.0].

RETURNS:

The interpolated rotation.

RETURN TYPE:

`Quaternion`

to_axis_angle()

Return the axis, angle representation of the quaternion.

RETURNS:

Axis, angle.

RETURN TYPE:

tuple[[Vector](#), float]

to_euler(order, euler_compat)

Return Euler representation of the quaternion.

PARAMETERS:

- **order** (*str*) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- **euler_compat** ([Euler](#)) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

RETURNS:

Euler representation of the quaternion.

RETURN TYPE:

[Euler](#)

to_exponential_map()

Return the exponential map representation of the quaternion.

This representation consist of the rotation axis multiplied by the rotation angle. Such a representation is useful for interpolation between multiple orientations.

RETURNS:

exponential map.

RETURN TYPE:

[Vector](#) of size 3

To convert back to a quaternion, pass it to the [Quaternion](#) constructor.

to_matrix()

Return a matrix representation of the quaternion.

RETURNS:

A 3x3 rotation matrix representation of the quaternion.

RETURN TYPE:

[Matrix](#)

to_swing_twist(axis)

Split the rotation into a swing quaternion with the specified axis fixed at zero, and the remaining twist rotation angle.

PARAMETERS:

axis (*str*) – Twist axis as a string in ['X', 'Y', 'Z'].

RETURNS:

Swing, twist angle.

RETURN TYPE:

tuple[[Quaternion](#), float]

angle

Angle of the quaternion.

TYPE:

float

axis

Quaternion axis as a vector.

TYPE:

Vector

is_frozen

True when this object has been frozen (read-only).

TYPE:

bool

is_valid

True when the owner of this data is valid.

TYPE:

bool

is_wrapped

True when this object wraps external data (read-only).

TYPE:

bool

magnitude

Size of the quaternion (read-only).

TYPE:

float

owner

The item this is wrapping or None (read-only).

w

Quaternion axis value.

TYPE:

float

x

Quaternion axis value.

TYPE:

float

y

Quaternion axis value.

TYPE:

float

z

Quaternion axis value.

TYPE:

float

class mathutils.Vector(seq)

This object gives access to Vectors in Blender.

PARAMETERS:

`seq(Sequence[float])` – Components of the vector, must be a sequence of at least two.

```
import mathutils

# zero length vector
vec = mathutils.Vector((0.0, 0.0, 1.0))

# unit length vector
vec_a = vec.normalized()

vec_b = mathutils.Vector((0.0, 1.0, 2.0))

vec2d = mathutils.Vector((1.0, 2.0))
vec3d = mathutils.Vector((1.0, 0.0, 0.0))
vec4d = vec_a.to_4d()

# Other `mathutils` types.
quat = mathutils.Quaternion()
matrix = mathutils.Matrix()

# Comparison operators can be done on Vector classes:

# (In)equality operators == and != test component values, e.g. 1,2,3 != 3,2,1
vec_a == vec_b
vec_a != vec_b

# Ordering operators >, >=, < and <= test vector length.
vec_a > vec_b
vec_a >= vec_b
vec_a < vec_b
vec_a <= vec_b

# Math can be performed on Vector classes
vec_a + vec_b
vec_a - vec_b
vec_a @ vec_b
vec_a * 10.0
matrix @ vec_a
quat @ vec_a
-vec_a

# You can access a vector object like a sequence
x = vec_a[0]
len(vec)
vec_a[:] = vec_b
vec_a[:] = 1.0, 2.0, 3.0
vec2d[:] = vec3d[:2]

# Vectors support 'swizzle' operations
# See https://en.wikipedia.org/wiki/Swizzling\_\(computer\_graphics\)
vec.xyz = vec.zyx
vec.xy = vec4d.zw
```

```
vec.xyz = vec4d.wzz  
vec4d.wxyz = vec.yxyx
```

classmethod Fill(size, fill=0.0)

Create a vector of length size with all values set to fill.

PARAMETERS:

- **size** (*int*) – The length of the vector to be created.
- **fill** (*float*) – The value used to fill the vector.

classmethod Linspace(start, stop, size)

Create a vector of the specified size which is filled with linearly spaced values between start and stop values.

PARAMETERS:

- **start** (*int*) – The start of the range used to fill the vector.
- **stop** (*int*) – The end of the range used to fill the vector.
- **size** (*int*) – The size of the vector to be created.

classmethod Range(start, stop, step=1)

Create a filled with a range of values.

PARAMETERS:

- **start** (*int*) – The start of the range used to fill the vector.
- **stop** (*int*) – The end of the range used to fill the vector.
- **step** (*int*) – The step between successive values in the vector.

classmethod Repeat(vector, size)

Create a vector by repeating the values in vector until the required size is reached.

PARAMETERS:

- **vector** (`mathutils.Vector`) – The vector to draw values from.
- **size** (*int*) – The size of the vector to be created.

angle(other, fallback=None)

Return the angle between two vectors.

PARAMETERS:

- **other** (`Vector`) – another vector to compare the angle with
- **fallback** (*Any*) – return this when the angle can't be calculated (zero length vector), (instead of raising a `ValueError`).

RETURNS:

angle in radians or fallback when given

RETURN TYPE:

float | Any

angle_signed(other, fallback=None)

Return the signed angle between two 2D vectors (clockwise is positive).

PARAMETERS:

- **other** (`Vector`) – another vector to compare the angle with
- **fallback** (*Any*) – return this when the angle can't be calculated (zero length vector), (instead of raising a `ValueError`).

RETURNS:

angle in radians or fallback when given

RETURN TYPE:

float | Any

copy()

Returns a copy of this vector.

RETURNS:

A copy of the vector.

RETURN TYPE:

`Vector`

Note

use this to get a copy of a wrapped vector with no reference to the original data.

cross(other)

Return the cross product of this vector and another.

PARAMETERS:

other (`Vector`) – The other vector to perform the cross product with.

RETURNS:

The cross product as a vector or a float when 2D vectors are used.

RETURN TYPE:

`Vector` | float

Note

both vectors must be 2D or 3D

dot(other)

Return the dot product of this vector and another.

PARAMETERS:

other (`Vector`) – The other vector to perform the dot product with.

RETURNS:

The dot product.

RETURN TYPE:

float

freeze()

Make this object immutable.

After this the object can be hashed, used in dictionaries & sets.

RETURNS:

An instance of this object.

lerp(other, factor)

Returns the interpolation of two vectors.

PARAMETERS:

- **other** (`Vector`) – value to interpolate with.
- **factor** (*float*) – The interpolation value in [0.0, 1.0].

RETURNS:

The interpolated vector.

RETURN TYPE:

`Vector`

negate()

Set all values to their negative.

normalize()

Normalize the vector, making the length of the vector always 1.0.

Warning

Normalizing a vector where all values are zero has no effect.

Note

Normalize works for vectors of all sizes, however 4D Vectors w axis is left untouched.

normalized()

Return a new, normalized vector.

RETURNS:

a normalized copy of the vector

RETURN TYPE:

`Vector`

orthogonal()

Return a perpendicular vector.

RETURNS:

a new vector 90 degrees from this vector.

RETURN TYPE:

`Vector`

Note

the axis is undefined, only use when any orthogonal vector is acceptable.

project(other)

Return the projection of this vector onto the *other*.

PARAMETERS:

other (`Vector`) – second vector.

RETURNS:

the parallel projection vector

RETURN TYPE:

`Vector`

reflect(mirror)

Return the reflection vector from the *mirror* argument.

PARAMETERS:

mirror (`Vector`) – This vector could be a normal from the reflecting surface.

RETURNS:

The reflected vector matching the size of this vector.

RETURN TYPE:

RETURN TYPE:

`Vector`

resize(size=3)

Resize the vector to have size number of elements.

resize_2d()

Resize the vector to 2D (x, y).

resize_3d()

Resize the vector to 3D (x, y, z).

resize_4d()

Resize the vector to 4D (x, y, z, w).

resized(size=3)

Return a resized copy of the vector with size number of elements.

RETURNS:

a new vector

RETURN TYPE:

`Vector`

rotate(other)

Rotate the vector by a rotation value.

Note

2D vectors are a special case that can only be rotated by a 2x2 matrix.

PARAMETERS:

other (`Euler` | `Quaternion` | `Matrix`) – rotation component of mathutils value

rotation_difference(other)

Returns a quaternion representing the rotational difference between this vector and another.

PARAMETERS:

other (`Vector`) – second vector.

RETURNS:

the rotational difference between the two vectors.

RETURN TYPE:

`Quaternion`

Note

2D vectors raise an `AttributeError`.

slerp(other, factor, fallback=None)

Returns the interpolation of two non-zero vectors (spherical coordinates).

PARAMETERS:

- **other** (`Vector`) – value to interpolate with.
- **factor** (*float*) – The interpolation value typically in [0.0, 1.0].
- **fallback** (*Any*) – return this when the vector can't be calculated (zero length vector or direct opposites), (instead of raising a `ValueError`).

RETURNS:

The interpolated vector.

RETURN TYPE:

`Vector`

to_2d()

Return a 2d copy of the vector.

RETURNS:

a new vector

RETURN TYPE:

`Vector`

to_3d()

Return a 3d copy of the vector.

RETURNS:

a new vector

RETURN TYPE:

`Vector`

to_4d()

Return a 4d copy of the vector.

RETURNS:

a new vector

RETURN TYPE:

`Vector`

to_track_quat(track, up)

Return a quaternion rotation from the vector and the track and up axis.

PARAMETERS:

- **track** (*str*) – Track axis in ['X', 'Y', 'Z', '-X', '-Y', '-Z'].
- **up** (*str*) – Up axis in ['X', 'Y', 'Z'].

RETURNS:

rotation from the vector and the track and up axis.

RETURN TYPE:

`Quaternion`

to_tuple(precision=-1)

Return this vector as a tuple with.

PARAMETERS:

precision (*int*) – The number to round the value to in [-1, 21].

RETURNS:

the values of the vector rounded by *precision*

RETURN TYPE:

`tuple[float, ...]`

zero()

Set all values to zero.

is_frozen

True when this object has been frozen (read-only).

TYPE:

bool

is_valid

True when the owner of this data is valid.

TYPE:

bool

is_wrapped

True when this object wraps external data (read-only).

TYPE:

bool

length

Vector Length.

TYPE:

float

length_squared

Vector length squared ($v \cdot v$).

TYPE:

float

magnitude

Vector Length.

TYPE:

float

owner

The item this is wrapping or None (read-only).

w

Vector W axis (4D Vectors only).

TYPE:

float

ww**TYPE:**

Vector

www**TYPE:**

Vector

www**TYPE:**

Vector

wwwx
TYPE:
Vector

wwwy
TYPE:
Vector

wwwz
TYPE:
Vector

wwx
TYPE:
Vector

wwwxw
TYPE:
Vector

wwwx
TYPE:
Vector

wwxy
TYPE:
Vector

wwxz
TYPE:
Vector

wwy
TYPE:
Vector

wwyw
TYPE:
Vector

wwyx
TYPE:
Vector

wwyy
TYPE:
Vector

wwyz
TYPE:
Vector

wwz

TYPE:
Vector

wwzw

TYPE:
Vector

wwzx

TYPE:
Vector

wwzy

TYPE:
Vector

wwzz

TYPE:
Vector

wx

TYPE:
Vector

wxw

TYPE:
Vector

wxww

TYPE:
Vector

wxwx

TYPE:
Vector

wxwy

TYPE:
Vector

wxwz

TYPE:
Vector

wxx

TYPE:
Vector

wxxw

TYPE:
Vector

wxxx

TYPE:

TYPE:
Vector

wxy

TYPE:
Vector

wxz

TYPE:
Vector

wy

TYPE:
Vector

wyw

TYPE:
Vector

wyx

TYPE:
Vector

wyy

TYPE:
Vector

wyz

TYPE:
Vector

wz

TYPE:
Vector

wzW

TYPE:
Vector

wzx

TYPE:
Vector

wzy

TYPE:
Vector

wzz

TYPE:
Vector

wy

TYPE:
Vector

vector

wyw

TYPE:

Vector

wyww

TYPE:

Vector

wywx

TYPE:

Vector

wywy

TYPE:

Vector

wywz

TYPE:

Vector

wyx

TYPE:

Vector

wyxx

TYPE:

Vector

wyxx

TYPE:

Vector

wyxy

TYPE:

Vector

wyxz

TYPE:

Vector

wyy

TYPE:

Vector

wyyw

TYPE:

Vector

wyyx

TYPE:

Vector

wyyy

TYPE:
Vector

wyyz

TYPE:
Vector

wyz

TYPE:
Vector

wyzw

TYPE:
Vector

wyzx

TYPE:
Vector

wyzy

TYPE:
Vector

wyzz

TYPE:
Vector

wz

TYPE:
Vector

wzw

TYPE:
Vector

wzww

TYPE:
Vector

wzwx

TYPE:
Vector

wzwy

TYPE:
Vector

wzwz

TYPE:
Vector

wzx

TYPE:
Vector

wxw

TYPE:
Vector

wxx

TYPE:
Vector

wxy

TYPE:
Vector

wxz

TYPE:
Vector

wzy

TYPE:
Vector

wzyw

TYPE:
Vector

wzyx

TYPE:
Vector

wzyy

TYPE:
Vector

wzyz

TYPE:
Vector

wzz

TYPE:
Vector

wzzw

TYPE:
Vector

wzzx

TYPE:
Vector

wzzy

TYPE:

Vector

wzz

TYPE:

Vector

x

Vector X axis.

TYPE:

float

xw

TYPE:

Vector

xww

TYPE:

Vector

xwww

TYPE:

Vector

xwwx

TYPE:

Vector

xwwy

TYPE:

Vector

xwwz

TYPE:

Vector

xwx

TYPE:

Vector

xwxw

TYPE:

Vector

xwxX

TYPE:

Vector

xwxy

TYPE:

Vector

xwxz

TYPE:

III E.

Vector

xwy

TYPE:

Vector

xwyw

TYPE:

Vector

xwyx

TYPE:

Vector

xwyy

TYPE:

Vector

xwyz

TYPE:

Vector

xwz

TYPE:

Vector

xwzw

TYPE:

Vector

xwzx

TYPE:

Vector

xwzy

TYPE:

Vector

xwzz

TYPE:

Vector

xx

TYPE:

Vector

xxw

TYPE:

Vector

xxww

TYPE:

Vector

Vector

xxwx

TYPE:

Vector

xxwy

TYPE:

Vector

xxwz

TYPE:

Vector

xxx

TYPE:

Vector

xxxw

TYPE:

Vector

xxxx

TYPE:

Vector

xxxy

TYPE:

Vector

xxxz

TYPE:

Vector

xyy

TYPE:

Vector

xyyw

TYPE:

Vector

xyyx

TYPE:

Vector

xyyy

TYPE:

Vector

xyyz

TYPE:

Vector

xxz

TYPE:
Vector

xxzw

TYPE:
Vector

xxx

TYPE:
Vector

xxzy

TYPE:
Vector

xxzz

TYPE:
Vector

xy

TYPE:
Vector

xyw

TYPE:
Vector

xyww

TYPE:
Vector

xywx

TYPE:
Vector

xywy

TYPE:
Vector

xywz

TYPE:
Vector

xyx

TYPE:
Vector

xyxw

TYPE:
Vector

xyxx

TYPE:
Vector

xyxy

TYPE:
Vector

xyxz

TYPE:
Vector

xyy

TYPE:
Vector

xyyw

TYPE:
Vector

xyyx

TYPE:
Vector

xyyy

TYPE:
Vector

xyyz

TYPE:
Vector

xyz

TYPE:
Vector

xyzw

TYPE:
Vector

xyzx

TYPE:
Vector

xyzy

TYPE:
Vector

xyzz

TYPE:
Vector

xz

TYPE:

Vector

xzw

TYPE:

Vector

xzww

TYPE:

Vector

xzwx

TYPE:

Vector

xzwy

TYPE:

Vector

xzwx

TYPE:

Vector

xzx

TYPE:

Vector

xzxw

TYPE:

Vector

xzxx

TYPE:

Vector

xzxy

TYPE:

Vector

xzxz

TYPE:

Vector

xzy

TYPE:

Vector

xzyw

TYPE:

Vector

xzyx

TYPE:

Vector

xzyy

TYPE:
Vector

xzyz

TYPE:
Vector

xzz

TYPE:
Vector

xzzw

TYPE:
Vector

xzzx

TYPE:
Vector

xzzy

TYPE:
Vector

xzzz

TYPE:
Vector

y

Vector Y axis.

TYPE:
float

yw

TYPE:
Vector

yww

TYPE:
Vector

ywww

TYPE:
Vector

ywwx

TYPE:
Vector

ywwy

TYPE:
Vector

ywwz

TYPE:

Vector

ywx

TYPE:

Vector

ywxw

TYPE:

Vector

ywx

TYPE:

Vector

ywx

TYPE:

Vector

ywxz

TYPE:

Vector

ywy

TYPE:

Vector

ywyw

TYPE:

Vector

ywyx

TYPE:

Vector

ywy

TYPE:

Vector

ywyz

TYPE:

Vector

ywz

TYPE:

Vector

ywzw

TYPE:

Vector

ywzx

TYPE:

Vector

ywzy

TYPE:

Vector

ywzz

TYPE:

Vector

yx

TYPE:

Vector

yxw

TYPE:

Vector

yxww

TYPE:

Vector

yxwx

TYPE:

Vector

yxwy

TYPE:

Vector

yxwz

TYPE:

Vector

yxx

TYPE:

Vector

yxxw

TYPE:

Vector

yxxx

TYPE:

Vector

yxyy

TYPE:

Vector

yxxz

TYPE:
Vector

yy

TYPE:
Vector

xyw

TYPE:
Vector

xyx

TYPE:
Vector

xyy

TYPE:
Vector

xyz

TYPE:
Vector

yxz

TYPE:
Vector

yxzw

TYPE:
Vector

yxzx

TYPE:
Vector

yxzy

TYPE:
Vector

yxzz

TYPE:
Vector

yy

TYPE:
Vector

yyw

TYPE:
Vector

yyww

TYPE:

Vector

yywx

TYPE:

Vector

yywy

TYPE:

Vector

yywz

TYPE:

Vector

yyx

TYPE:

Vector

yyxw

TYPE:

Vector

yyxx

TYPE:

Vector

yyxy

TYPE:

Vector

yyxz

TYPE:

Vector

yyy

TYPE:

Vector

yyyw

TYPE:

Vector

yyyx

TYPE:

Vector

yyyy

TYPE:

Vector

yyyz

TYPE:

Vector

yyz

TYPE:
Vector

yyzw

TYPE:
Vector

yyzx

TYPE:
Vector

yyzy

TYPE:
Vector

yyzz

TYPE:
Vector

yz

TYPE:
Vector

yzw

TYPE:
Vector

yzww

TYPE:
Vector

yzwx

TYPE:
Vector

yzwy

TYPE:
Vector

yzwz

TYPE:
Vector

yzx

TYPE:
Vector

yzxw

TYPE:
Vector

yzxx

TYPE:
Vector

yzxy

TYPE:
Vector

yzxz

TYPE:
Vector

zyy

TYPE:
Vector

zyyw

TYPE:
Vector

zyyx

TYPE:
Vector

zyyy

TYPE:
Vector

zyyz

TYPE:
Vector

yyz

TYPE:
Vector

yyzw

TYPE:
Vector

yyzx

TYPE:
Vector

yyzy

TYPE:
Vector

yyzz

TYPE:
Vector

z

Vector Z axis (3D Vectors only).

TYPE:

float

zw

TYPE:

Vector

zww

TYPE:

Vector

zwww

TYPE:

Vector

zwwx

TYPE:

Vector

zwwy

TYPE:

Vector

zwwz

TYPE:

Vector

zwx

TYPE:

Vector

zwxw

TYPE:

Vector

zwxX

TYPE:

Vector

zwxY

TYPE:

Vector

zwxZ

TYPE:

Vector

zwy

TYPE:

Vector

zwyw

TYPE:
Vector

zw_yx

TYPE:
Vector

zw_yy

TYPE:
Vector

zw_yz

TYPE:
Vector

zw_z

TYPE:
Vector

zw_zw

TYPE:
Vector

zw_zx

TYPE:
Vector

zw_zy

TYPE:
Vector

zw_zz

TYPE:
Vector

zx

TYPE:
Vector

zx_w

TYPE:
Vector

zx_ww

TYPE:
Vector

zx_wx

TYPE:
Vector

zx_wy

TYPE:
Vector

vector

\mathbb{XWZ}

TYPE:

Vector

\mathbb{XX}

TYPE:

Vector

\mathbb{XXW}

TYPE:

Vector

\mathbb{XXX}

TYPE:

Vector

\mathbb{XXy}

TYPE:

Vector

\mathbb{XXZ}

TYPE:

Vector

\mathbb{Xy}

TYPE:

Vector

\mathbb{Xyw}

TYPE:

Vector

\mathbb{Xyx}

TYPE:

Vector

\mathbb{Xyy}

TYPE:

Vector

\mathbb{Xyz}

TYPE:

Vector

\mathbb{XZ}

TYPE:

Vector

\mathbb{XZW}

TYPE:

Vector

xxz

TYPE:
Vector

xyz

TYPE:
Vector

xxz

TYPE:
Vector

zy

TYPE:
Vector

zyw

TYPE:
Vector

zyww

TYPE:
Vector

zywx

TYPE:
Vector

zywy

TYPE:
Vector

zywz

TYPE:
Vector

zyx

TYPE:
Vector

zyxw

TYPE:
Vector

zyxx

TYPE:
Vector

zyxy

TYPE:
Vector

zyxz

TYPE:
Vector

zy

TYPE:
Vector

zyw

TYPE:
Vector

zyx

TYPE:
Vector

zyy

TYPE:
Vector

zyz

TYPE:
Vector

yz

TYPE:
Vector

yzw

TYPE:
Vector

yzx

TYPE:
Vector

zyzy

TYPE:
Vector

zyzz

TYPE:
Vector

zz

TYPE:
Vector

zzw

TYPE:
Vector

zzww

TYPE:

Vector

zwx

TYPE:

Vector

zwy

TYPE:

Vector

zww

TYPE:

Vector

zx

TYPE:

Vector

zxw

TYPE:

Vector

zxx

TYPE:

Vector

zxy

TYPE:

Vector

zxz

TYPE:

Vector

zy

TYPE:

Vector

zyw

TYPE:

Vector

zyx

TYPE:

Vector

zzy

TYPE:

Vector

zyz

TYPE:

Vector

zzz

TYPE:

Vector

zzw

TYPE:

Vector

zzx

TYPE:

Vector

zzy

TYPE:

Vector

zzz

TYPE:

Vector