

[Skip to content](#)

MaterialSlot(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MaterialSlot(bpy_struct)`

Material slot in an object

link

Link material to object or the object's data

TYPE:

enum in ['OBJECT', 'DATA'], default 'DATA'

material

Material data-block used by this material slot

TYPE:

`Material`

name

Material slot name

TYPE:

string, default '', (readonly, never None)

slot_index

TYPE:

int in [-inf, inf], default 0, (readonly)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `bpy.context.material_slot` • `Object.material_slots`