

[Skip to content](#)

MaskSplinePointUW(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MaskSplinePointUW(bpy_struct)`

Single point in spline segment defining feather

select

Selection status

TYPE:

boolean, default False

u

U coordinate of point along spline segment

TYPE:

float in [0, 1], default 0.0

weight

Weight of feather point

TYPE:

float in [0, 1], default 0.0

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.id_properties_clear
- bpy_struct.id_properties_ensure
- bpy_struct.id_properties_ui
- bpy_struct.is_property_hidden
- bpy_struct.is_property_overridable_library
- bpy_struct.is_property_readonly
- bpy_struct.is_property_set
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.pop
- bpy_struct.property_overridable_library_set
- bpy_struct.property_unset
- bpy_struct.type_recast
- bpy_struct.values

References

- `MaskSplinePoint.feather_points`