

CacheFileLayers(bpy_struct)

base class — `bpy_struct`

class `bpy.types.CacheFileLayers(bpy_struct)`

Collection of cache layers

active

Active layer of the CacheFile

TYPE:

`CacheFileLayer`

new(filepath)

Add a new layer

PARAMETERS:

filepath (*string, (never None)*) – File path to the archive used as a layer

RETURNS:

Newly created layer

RETURN TYPE:

`CacheFileLayer`

remove(layer)

Remove an existing layer from the cache file

PARAMETERS:

layer (`CacheFileLayer`, (never None)) – Layer to remove

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `CacheFile.layers`