## Skip to content ShaderNodeSeparateRGB(ShaderNode)

```
base classes — bpy_struct, Node, NodeInternal, ShaderNode
class bpy.types.ShaderNodeSeparateRGB(ShaderNode)
    Deprecated
    classmethod is_registered_node_type()
        True if a registered node type
        RETURNS:
            Result
        RETURN TYPE:
            boolean
    classmethod input template(index)
        Input socket template
        PARAMETERS:
            index (int in [0, inf]) – Index
        RETURNS:
            result
        RETURN TYPE:
             NodeInternalSocketTemplate
    class method output template (index)
        Output socket template
        PARAMETERS:
            index (int in [0, inf]) – Index
        RETURNS:
            result
        RETURN TYPE:
             NodeInternalSocketTemplate
    classmethod bl rna get subclass(id, default=None)
        PARAMETERS:
            id (str) – The RNA type identifier.
        RETURNS:
            The RNA type or default when not found.
        RETURN TYPE:
             bpy.types.Struct subclass
    classmethod bl rna get subclass py(id, default=None)
        PARAMETERS:
            id (str) – The RNA type identifier.
        RETURNS:
            The class or default when not found.
```

tyne

**RETURN TYPE:** 

## **Inherited Properties**

- bpy struct.id data
- Node.type
- Node.location
- Node.location absolute Node.hide
- Node.width
- Node.height
- Node.dimensions
- Node.name
- Node.label
- Node.inputs
- Node.outputs
- Node.internal links
- Node.parent
- Node.warning\_propagation Node.bl\_width\_max
- Node.use custom color Node.bl height default
- Node.color
- Node.color\_tag

- Node.select
- Node.show options
- Node.show preview
- Node.mute
- Node.show texture
- Node.bl idname
  - Node.bl label
- Node.bl description
- Node.bl icon
- Node.bl static type
- Node.bl width default
  - Node.bl width min
- Node.bl height min
- Node.bl\_height\_max

## **Inherited Functions**

- bpy struct.as pointer
- bpy struct.driver add
- bpy struct.driver remove
- bpy\_struct.get
- bpy struct.id properties clear
- bpy struct.id properties ensure
- bpy struct.id properties ui
- bpy\_struct.is\_property\_hidden
- bpy\_struct.is\_property\_overridable\_library
- bpy struct.is property readonly
- bpy struct.is property set
- bpy struct.items
- bpy struct.keyframe delete
- bpy\_struct.keyframe\_insert
- bpy struct.keys
- bpy struct.path from id
- bpy\_struct.path\_resolve
- bpy struct.pop
- bpy\_struct.property\_overridable\_library\_set
- bpy struct.property unset
- bpy struct.type\_recast
- bpy\_struct.values
- Node.socket value update
- Node.is registered node type

- Node.poll instance
- Node.update
- Node.insert link
- Node.init
- Node.copy
- Node.free
- Node.draw buttons
- Node.draw buttons ext
- Node.draw label
- Node.debug zone body lazy function graph
- Node.debug\_zone\_lazy\_function\_graph
- Node.poll
- Node.bl\_rna\_get\_subclass
- Node.bl rna get subclass py
- NodeInternal.poll
- NodeInternal.poll instance
- NodeInternal.update
- NodeInternal.draw buttons
- NodeInternal.draw buttons ext
- NodeInternal.bl rna get subclass
- NodeInternal.bl\_rna\_get\_subclass\_py
- ShaderNode.poll
- ShaderNode.bl\_rna\_get\_subclass

• Node.poll

Previous ShaderNodeSeparateHSV(ShaderNode) Report issue on this page Copyright © Blender Authors

Made with Furo

No ShaderNodeSeparateXYZ(ShaderNoc