PreferencesExtensions(bpy_struct)

base class — `bpy_struct`

class bpy.types.**PreferencesExtensions(bpy_struct)**

> Settings for extensions

> **active_repo**
>
> > Index of the extensions repository being edited in the Preferences UI
> >
> > **TYPE:**
> >
> > > int in [-32768, 32767], default 0
>
> **repos**
>
> > **TYPE:**
> >
> > > `UserExtensionRepoCollection` `bpy_prop_collection` of `UserExtensionRepo`, (readonly)
>
> **use_online_access_handled**
>
> > The user has been shown the "Online Access" prompt and make a choice
> >
> > **TYPE:**
> >
> > > boolean, default False
>
> **classmethod bl_rna_get_subclass(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The RNA type or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > `bpy.types.Struct` subclass
>
> **classmethod bl_rna_get_subclass_py(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The class or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > type

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Preferences.extensions`

Report issue on this page