

[Skip to content](#)

SurfaceDeformModifier(Modifier)

base classes — [bpy_struct](#), [Modifier](#)

class bpy.types.SurfaceDeformModifier(Modifier)

falloff

Controls how much nearby polygons influence deformation

TYPE:

float in [2, 16], default 4.0

invert_vertex_group

Invert vertex group influence

TYPE:

boolean, default False

is_bound

Whether geometry has been bound to target mesh

TYPE:

boolean, default False, (readonly)

strength

Strength of modifier deformations

TYPE:

float in [-100, 100], default 1.0

target

Mesh object to deform with

TYPE:

[Object](#)

use_sparse_bind

Only record binding data for vertices matching the vertex group at the time of bind

TYPE:

boolean, default False

vertex_group

Vertex group name for selecting/weighting the affected areas

TYPE:

string, default "", (never None)

classmethod bl_ma_get_subclass(id, default=None)

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

[bpy.types.Struct](#) subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.type`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.show_in_editmode`
- `Modifier.show_on_cage`
- `Modifier.show_expanded`
- `Modifier.is_active`
- `Modifier.use_pin_to_last`
- `Modifier.is_override_data`
- `Modifier.use_apply_on_spline`
- `Modifier.execution_time`
- `Modifier.persistent_uid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Modifier.bl_rna_get_subclass`
- `Modifier.bl_rna_get_subclass_py`