

[Skip to content](#)

IDOverrideLibraryProperty(bpy_struct)

base class — [bpy_struct](#)

class `bpy.types.IDOverrideLibraryProperty(bpy_struct)`

Description of an overridden property

operations

List of overriding operations for a property

TYPE:

`IDOverrideLibraryPropertyOperations` `bpy_prop_collection` of
`IDOverrideLibraryPropertyOperation`, (readonly)

ma_path

RNA path leading to that property, from owning ID

TYPE:

string, default "", (readonly, never None)

classmethod `bl_rna_get_subclass(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

`bpy.types.Struct` subclass

classmethod `bl_rna_get_subclass_py(id, default=None)`

PARAMETERS:

id (*str*) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.id_properties_clear](#)
- [bpy_struct.id_properties_ensure](#)
- [bpy_struct.id_properties_ui](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.pop](#)

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `IDOverrideLibrary.properties`
- `IDOverrideLibraryProperties.add`
- `IDOverrideLibraryProperties.remove`

[Previous](#)
[IDOverrideLibraryProperties\(bpy_struct\)](#)
[Report issue on this page](#)

Copyright © Blender Authors
 Made with [Furo](#)

[Next](#)
[IDOverrideLibraryPropertyOperation\(bpy_struct\)](#)