CURVES_UL_attributes(UIList)

base classes — `bpy_struct`, `UIList`

class bpy.types.**CURVES_UL_attributes(UIList)**

> **draw_item(_context, layout, _data, attribute, _icon, _active_data, _active_propname, _index)**
>
> **filter_items(_context, data, property)**
>
> **classmethod bl_rna_get_subclass(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The RNA type or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > `bpy.types.Struct` subclass
>
> **classmethod bl_rna_get_subclass_py(id, default=None)**
>
> > **PARAMETERS:**
> >
> > > **id** (*str*) – The RNA type identifier.
> >
> > **RETURNS:**
> >
> > > The class or default when not found.
> >
> > **RETURN TYPE:**
> >
> > > type

Inherited Properties

- `bpy_struct.id_data`
- `UIList.bl_idname`
- `UIList.list_id`
- `UIList.layout_type`
- `UIList.use_filter_show`
- `UIList.filter_name`
- `UIList.use_filter_invert`
- `UIList.use_filter_sort_alpha`
- `UIList.use_filter_sort_reverse`
- `UIList.use_filter_sort_lock`
- `UIList.bitflag_filter_item`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overridable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`
- `bpy_struct.property_overridable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `UIList.draw_item`
- `UIList.draw_filter`
- `UIList.filter_items`
- `UIList.append`

Report issue on this page