

Ex.No: 12

Date:  
3.11.25**Implementing Map Side Join in MapReduce****Aim:**

To implement a **Map-Side Join** using Hadoop MapReduce for joining a large dataset with a small lookup dataset using the Distributed Cache mechanism

**Procedure:****1. Prepare input files:**

customers.txt (Small file to be distributed)

C101,John

C102,Mary

C103,Steve

orders.txt (Large file)

O1001,C101,500

O1002,C102,1000

O1003,C103,300

**2. Add the small file to HDFS:**

```
hdfs dfs -mkdir /input
```

```
hdfs dfs -put orders.txt /input/
```

```
hdfs dfs -put customers.txt /input/
```

**3. Compilation and Execution:****Compile and Create JAR:**

```
javac -classpath $(hadoop classpath) -d . MapSideJoinMapper.java MapSideJoinDriver.java
```

```
jar -cf mapjoin.jar *
```

**Run MapReduce Job:**

```
hadoop jar mapjoin.jar MapSideJoinDriver
```

**4. View Output:**

```
hdfs dfs -cat /output_mapjoin/part-m-00000
```

**Program:****MapSideJoinMapper.java :**

```
import java.io.*;
```

```
import java.util.HashMap;
```

```
import org.apache.hadoop.io.*;
```

```
import org.apache.hadoop.fs.Path;
```

```
import org.apache.hadoop.mapreduce.*;
import org.apache.hadoop.conf.Configuration;

public class MapSideJoinMapper extends Mapper<LongWritable, Text, Text, Text> {

    private HashMap<String, String> customerMap = new HashMap<>();
    private Text outputKey = new Text();
    private Text outputValue = new Text();

    @Override
    protected void setup(Context context) throws IOException {
        Path[] cacheFiles = context.getLocalCacheFiles();
        BufferedReader reader = new BufferedReader(new
        FileReader(cacheFiles[0].toString()));

        String line;
        while ((line = reader.readLine()) != null) {
            String[] parts = line.split(",");
            customerMap.put(parts[0], parts[1]); // C101 → John
        }
        reader.close();
    }

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {

        String[] parts = value.toString().split(",");
        String orderId = parts[0];
        String custId = parts[1];
        String amount = parts[2];

        String custName = customerMap.get(custId);
```

```
    if (custName != null) {  
        outputKey.set(orderId);  
        outputValue.set(custName + "," + amount);  
        context.write(outputKey, outputValue);  
    }  
}  
}
```

**Driver Class:**

```
import org.apache.hadoop.conf.Configuration;  
import org.apache.hadoop.fs.Path;  
import org.apache.hadoop.io.Text;  
import org.apache.hadoop.mapreduce.Job;  
import org.apache.hadoop.mapreduce.lib.input.*;  
import org.apache.hadoop.mapreduce.lib.output.*;  
  
public class MapSideJoinDriver {  
    public static void main(String[] args) throws Exception {  
        Configuration conf = new Configuration();  
        Job job = Job.getInstance(conf, "Map Side Join");  
  
        job.setJarByClass(MapSideJoinDriver.class);  
        job.setMapperClass(MapSideJoinMapper.class);  
        job.setNumReduceTasks(0); // No reducer  
        job.setOutputKeyClass(Text.class);  
        job.setOutputValueClass(Text.class);  
  
        // Add customers.txt to distributed cache  
        job.addCacheFile(new Path("/input/customers.txt").toUri());  
  
        FileInputFormat.addInputPath(job, new Path("/input/orders.txt"));  
        FileOutputFormat.setOutputPath(job, new Path("/output_mapjoin"));  
  
        System.exit(job.waitForCompletion(true) ? 0 : 1);  
    }  
}
```

```
}  
}
```

**Output:**

```
O1001  John,500  
O1002  Mary,1000  
O1003  Steve,300
```

**Result:**

Map-side join was successfully implemented using the Distributed Cache. The join was performed in the Mapper, improving performance by avoiding the shuffle and reduce phases.