



# Polars cheat sheet



## General

### Install

```
pip install polars
```



### Import

```
import polars as pl
```

## Creating/reading DataFrames

### Create DataFrame

nrs	names	random	groups
1	"foo"	0.3	"A"
2	"ham"	0.7	"A"
3	"spam"	0.1	"B"
null	"egg"	0.9	"C"
5	null	0.6	"B"

```
df = pl.DataFrame({
    "nrs": [1, 2, 3, None, 5],
    "names": ["foo", "ham", "spam", "egg", None],
    "random": [0.3, 0.7, 0.1, 0.9, 0.6],
    "groups": ["A", "A", "B", "C", "B"],
})
```

### Read CSV

```
df = pl.read_csv("https://j.mp/iris.csv",
    has_header=True)
```

### Read parquet

```
df = pl.read_parquet("path.parquet")
```


## Expressions

Polars expressions can be performed in sequence. This improves readability of code.

```
df \
    .filter(pl.col("nrs") < 4) \
    .groupby("groups") \
    .agg(
        pl \
            .all() \
            .sum()
    )
```

by Franz Diebold ([diebold.io](https://diebold.io))

## Subset Observations - rows



Filter: Extract rows that meet logical criteria.

```
df.filter(pl.col("random") > 0.5)
df.filter(
    (pl.col("groups") == "B")
    & (pl.col("random") > 0.5)
)
```

### Sample

```
# Randomly select fraction of rows.
df.sample(frac=0.5)

# Randomly select n rows.
df.sample(n=2)
```

### Select first and last rows

```
# Select first n rows
df.head(n=2)

# Select last n rows.
df.tail(n=2)
```

## Subset Variables - columns



### Select multiple columns with specific names

```
df.select(["nrs", "names"])
```

### Select columns whose name matches regex

```
df.select(pl.col("^n.*$"))
```

## Subsets - rows and columns



### Select rows 2-4

```
df[2:4, :]
```

### Select columns in positions 1 and 3 (first column is 0)


```
df[:, [1, 3]]
```

## Reshaping Data – Change layout, sorting, renaming



### Append rows of DataFrames

```
pl.concat([df, df2])
```



### Append columns of DataFrames

```
pl.concat([df, df3], how="horizontal")
```

### Gather columns into rows

```
df.melt(
    id_vars=["nrs", "names"],
    value_vars=["random", "groups"]
)
```

### Spread rows into columns

```
df.pivot(values="nrs", index="groups",
    columns="names")
```

### Order rows by values of a column

```
# low to high
df.sort("random")
```

```
# high to low
df.sort("random", reverse=True)
```

### Rename the columns of a DataFrame

```
df.rename({"nrs": "idx"})
```

### Drop columns from DataFrame

```
df.drop(["names", "random"])
```