



# Polars cheat sheet



## General

### Install

```
pip install polars
```

### Import

```
import polars as pl
```

## Creating/reading DataFrames

### Create DataFrame

nrs	names	random	groups
1	"foo"	0.3	"A"
2	"ham"	0.7	"A"
3	"spam"	0.1	"B"
null	"egg"	0.9	"C"
5	null	0.6	"B"

```
df = pl.DataFrame({
    "nrs": [1, 2, 3, None, 5],
    "names": ["foo", "ham", "spam", "egg", None],
    "random": [0.3, 0.7, 0.1, 0.9, 0.6],
    "groups": ["A", "A", "B", "C", "B"],
})
```

### Read CSV

```
df = pl.read_csv("https://j.mp/iris.csv",
    has_header=True)
```

### Read parquet

```
df = pl.read_parquet("path.parquet",
    columns=["select", "column:"
```


## Expressions

Polars expressions can be performed in sequence. This improves readability of code.

```
df \
    .filter(pl.col("nrs") < 4) \
    .groupby("groups") \
    .agg(
        pl \
            .all() \
            .sum()
    )
```

by Franz Diebold ([diebold.io](https://github.com/dieboldio))

## Subset Observations - rows



Filter: Extract rows that meet logical criteria.

```
df.filter(pl.col("random") > 0.5)
df.filter(
    (pl.col("groups") == "B")
    & (pl.col("random") > 0.5)
)
```

### Sample

```
# Randomly select fraction of rows.
df.sample(frac=0.5)

# Randomly select n rows.
df.sample(n=2)
```

### Select first and last rows

```
# Select first n rows
df.head(n=2)

# Select last n rows.
df.tail(n=2)
```

## Subset Variables - columns




### Select multiple columns with specific names

```
df.select(["nrs", "names"])
```

### Select columns whose name matches regex

```
df.select(pl.col("^n.*$"))
```

## Subsets - rows and columns



### Select rows 2-4

```
df[2:4, :]
```

### Select columns in positions 1 and 3 (first column is 0)


```
df[:, [1, 3]]
```

## Reshaping Data – Change layout, sorting, renaming



### Append rows of DataFrames

```
pl.concat([df, df2])
```



### Append columns of DataFrames

```
pl.concat([df, df3], how="horizontal")
```



### Gather columns into rows

```
df.melt(
    id_vars="nrs",
    value_vars=["names", "groups"]
)
```



### Spread rows into columns

```
df.pivot(values="nrs", index="groups",
    columns="names")
```

### Order rows by values of a column

```
# low to high
df.sort("random")

# high to low
df.sort("random", reverse=True)
```

### Rename the columns of a DataFrame

```
df.rename({"nrs": "idx"})
```

### Drop columns from DataFrame

```
df.drop(["names", "random"])
```

## Summarize Data

Count number of rows with each unique value of variable

```
df["groups"].value_counts()
```

# of rows in DataFrame


```
len(df)
# or
df.height
```

Tuple of # of rows, # of columns in DataFrame

```
df.shape
```

# of distinct values in a column

```
df["groups"].n_unique()
```



Basic descriptive and statistics for each column

```
df.describe()
```

### Aggregation functions

```
df.select(
    [
        # Sum values
        pl.sum("random").alias("sum"),

        # Minimum value
        pl.min("random").alias("min"),

        # Maximum value
        pl.max("random").alias("max"),
        # or
        pl.col("random").max().alias("other_max"),

        # Standard deviation
        pl.std("random").alias("std dev"),

        # Variance
        pl.var("random").alias("variance"),


        # Median
        pl.median("random").alias("median"),

        # Mean
        pl.mean("random").alias("mean"),

        # Quantile
        pl.quantile("random", 0.75) \
            .alias("quantile_0.75"),
        # or
        pl.col("random").quantile(0.75) \
            .alias("other_quantile_0.75"),

        # First value
        pl.first("random").alias("first"),
    ]
)
```

## Group Data



Group by values in column named "col", returning a GroupBy object

```
df.groupby("groups")
```

All of the aggregation functions from above can be applied to a group as well

```
df.groupby(by="groups").agg([
    # Sum values
    pl.sum("random").alias("sum"),

    # Minimum value
    pl.min("random").alias("min"),

    # Maximum value
    pl.max("random").alias("max"),
    # or
    pl.col("random").max().alias("other_max"),

    # Standard deviation
    pl.std("random").alias("std_dev"),

    # Variance
    pl.var("random").alias("variance"),

    # Median
    pl.median("random").alias("median"),

    # Mean
    pl.mean("random").alias("mean"),

    # Quantile
    pl.quantile("random", 0.75) \
        .alias("quantile_0.75"),
    # or
    pl.col("random").quantile(0.75) \
        .alias("other_quantile_0.75"),

    # First value
    pl.first("random").alias("first"),
])
```

Additional GroupBy functions

```
df.groupby(by="groups").agg([
    # Count the number of values in each group
    pl.count("random").alias("size"),

    # Sample one element in each group
    pl.col("names").apply(
        lambda group_df: group_df.sample(1)
    ),
])
```

## Handling Missing Data

Drop rows with any column having a null value [↗](#)

```
df.drop_nulls()
```


Replace null values with given value [↗](#)

```
df.fill_null(42)
```

Replace floating point NaN values with given value [↗](#)

```
df.fill_nan(42)
```

## Make New Columns



Add a new columns to the DataFrame [↗](#)

```
df.with_column(
    (pl.col("random") * pl.col("nrs")) \
        .alias("product")
)
```

Add several new columns to the DataFrame [↗](#)

```
df.with_columns([
    (pl.col("random") * pl.col("nrs")) \
        .alias("product"),
    pl.col("names").str.lengths() \
        .alias("names_lengths"),
])
```

Add a column at index 0 that counts the rows [↗](#)

```
df.with_row_count()
```

## Rolling Functions

The following rolling functions are available

```
df.select([
    # Rolling maximum value
    pl.col("random") \
        .rolling_max(window_size=2) \
        .alias("rolling_max"),

    # Rolling mean value
    pl.col("random") \
        .rolling_mean(window_size=2) \
        .alias("rolling_mean"),

    # Rolling median value
    pl.col("random") \
        .rolling_median(
            window_size=2, min_periods=2) \
        .alias("rolling_median"),

    # Rolling minimum value
    pl.col("random") \
        .rolling_min(window_size=2) \
        .alias("rolling_min"),

    # Rolling standard deviation
    pl.col("random") \
        .rolling_std(window_size=2) \
        .alias("rolling_std"),

    # Rolling sum values
    pl.col("random") \
        .rolling_sum(window_size=2) \
        .alias("rolling_sum"),

    # Rolling variance
    pl.col("random") \
        .rolling_var(window_size=2) \
        .alias("rolling_var"),

    # Rolling custom function
    pl.col("random") \
        .rolling_apply(
            function=np.nanstd, window_size=2) \
        .alias("rolling_apply"),
])
```